ſ	I G I M C		0	8 >		]
4						4
ω			LAYOUT SHOWN AS EXAMPL	.E		3
	Keying Shown as example					
	CHARACTERISTICS Connector dimension					
	-Standard : Based on MIL-DTL-38999 Series III Dim Nominal					
	Shell Material: AluminiumØS35.7 Max-Shell Plating: Olive drab CadmiumZ31 Max-Insulator: ThermoplasticVV THREADM25x1-6g-Contacts: Copper Alloy: MaxImage: Comparison of the second sec	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
		Country Jurisdiction & Control List				
	-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories	FR   Not Listed     PN: 8D517W06AD				2
	-Temperature Range - 65°C to +175°C	A 17-10-2016	5 First Release			
	-Salt Spray : 500 hours	ISS DATE	Latest modification - by		MOD N°	-
	-Mass : 29.9 g ± 10%	Designed By:	Date:	CUSTOMER DRAWING		
		TITLE	Aluminium	Plug 8D series		
_	BASIC SERIES:     8D     5     -     17     W     06     A     D       SHELL TYPE     : Plug with RFI Shielding     -     17     W     06     A     D	SCALE NA	General linear Tolerances:	NPRDS / PROJECT <b>859</b>		1
	CONTACT TYPE     : Standard Crimp Contact       SHELL SIZE : 17     CONTACT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURIAU.COM	This document is the proper SOURIAU it must not be reproduced communicated without perm	lor	
	PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 17-06	FORMAT	SOURIAU DR		SHEET	-
1		A3	8D517W06A		1/2	
		7.0			1/2	

r	т	G	г –	m	Ū	0
		Contact Layout				
4	-x -	$ \overset{+Y}{\bigoplus} $				
_		Contacts (Insert arrangement 17-6)				
ω	Conta position A B C C D E F	(mm)         (mm)           +.121 (3.07)         +.209 (5.31)           +.241 (6.12)         +.000 (0.00)           +.000 (0.00)        241 (6.12)          241 (6.12)         +.000 (0.00)          121 (3.07)         +.209 (5.31)				
	size no. co	mber of Size Service Contact Supersedes ntacts contacts rating location 6 12 I All MS20053-6				
	F					SOURIAU shall not be liable for an
						due to a use of the Products wi the Specifications issued by either o (professional recommenda
N						PN: 8D517
					A 17-10-20	016 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
<u> </u>					SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.C
				_	FORMAT A3	SOURIAU 8D517W
L	Н	G	F	E	D	C

Ξ		A				
				4		
				3		
any non-conformit which does not co r of the Parties or b dation, technical n ntry Jurisc R 7W06AD	mply with by a third party	List		2		
			/OD N°			
	CUSTOMER D	1				
ninium Plug 8D series						
NPRDS / PROJECT 859						
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
U DRG N° W06AD-C			SHEET 2/2			
B		A				