


REV	MODIFICATION	UPDATE DATE	SIGNATURE



Cable Length	Tolerance
Cable Length < 1M	5cm
1M ≤ Cable Length < 15M	10cm
15M ≤ Cable Length < 30M	15cm
Cable Length ≥ 30M	Cable Length * 1%

Technical requirements:
 1. Performance requirements:
 Insertion loss: $IL \leq 0.2\text{dB}$
 Return loss: $RL \geq 60\text{dB}$
 2. Fiber optic connectors meet IEC 61754, YDT1272 standards
 3. Optical fiber cable in line with IEC60793-1, IEC 60794 standards
 4. Fiber optic jumper complies with IEC 61300, GR-326, TIA/EIA568-B standards

Requirements Of Cable					
Cable Type				Fiber Type	G657A1
Cable Diameter	0.9mm	Attenuation	@1310nm $\leq 0.32\text{dB/km}$		
Cable Material	PVC		@1550nm $\leq 0.18\text{dB/km}$		
Tensile Strength	Long Term	3 N	Crush Resistance	Long Term	/
	Short Term	6 N		Short Term	/
Bending Radius	Static	3.0mm	Temperature Range	Storage Temperature	-20°C ~ +70°C
	Dynamic	5.0mm		Operating Temperature	-20°C ~ +70°C

2	12	LC/APC SM 0.9mm Simplex Connector(Green Housing Green Boot)	
1	A/R	Ø:0.9mm , Singlemode 9/125 G657A1, Tight Buffer, Simplex, Fiber Optic Cable, Corning Fiber, PVC, 12 Colors	
ITEM	QTY	P/N	SPECIFICATIONS



DRAW		DATE	29-09-2021	TITLE: Pigtail LC/APC Simplex 0.9mm Singlemode 12 Fiber					
CHECK	<i>Lihuanhuan</i>	APPROVED		CUSTOMER NO		DWG NO	FJ9LCAX-12FR-XXM-900	REV	A