

(PART B)

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 832FX-B

Other Means of Identification: Black Flexible Epoxy Encapsulating and Potting Compound (Part B)

Related Part # 832FX-450ML, 832FX-1.7L, 832FX-7.4L, 832FX-40L

Recommended Use and Restriction on Use

Use: Epoxy hardener for use with resins

Uses Advised Against: Not for use as a spray coating

Details of Manufacturer or Importer

Manufacturer MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

***** +1-800-340-0772
 Fax +1-800-340-0773
 E-MAIL <u>support@mgchemicals.com</u>

 WEB

 www.mgchemicals.com

***** +1-905-331-1396

 Fax
 +1-905-331-2682

 E-MAIL

 info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962** (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

Page **1** of **16**



832FX-B

(PART B)

Section 2: Hazard(s) Identification

Classification of the Chemical Material

GHS Categories

Criteria		Category	Signal Word	Pictograms
Serious Eye Damage		1	Danger	Corrosion
Skin Corrosion		1	Danger	Corrosion
Sensitization	Skin sensitizer	1	Warning	Exclamation
Acute Toxicity	Oral	4	Warning	Exclamation
Specific Target Organ Toxicity	Repeated Exposure	2	Warning	Health
Environmental Hazard	Chronic Aqua. Tox.	1	Warning	Environment

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
Le contraction de la contracti	H314: Causes severe skin burns and eye damage
^	H317: May cause an allergic skin reaction
	H302: Harmful if swallowed
	H373: May cause damage to liver and immune system through prolonged or repeated exposure

Section continued on the next page

Page 2 of 16



(PART B)

Pictograms	Hazard Statements
	H410: Very toxic to aquatic life with long lasting effects
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P260	Do not breathe fumes/mist/vapors.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
Response	Precautionary Statements
P314	Get medical advice/attention if you feel unwell.
P305 + P351 + P338, P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P303 + P361 + P353, P310	IF ON SKIN (or hair): Take off immediately all contaminated clothing Rinse skin with water [or shower]. Immediately call a POISON CENTER/doctor
P363	Wash contaminated clothing before reuse.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P301 + P330 + P331, P310	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.
P304 + P340, P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P391	Collect spillage.

Section continued on the next page

Page ${\bf 3}$ of ${\bf 16}$



(PART B)

Continued	
Storage	Precautionary Statements
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
9046-10-0	polyoxypropylene diamine	59%
61788-44-1	phenol, styrenated	20%
61788-46-3	amines, coco alkyl	9%
25620-58-0	trimethylhexamethylenediamine	9%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	2%

Section 4: First-Aid Measures

Exposure Condition	GHS Code: Precautionary Statement
IF IN EYES	P305 + P351 + P338, P310
Immediate Symptoms	redness, severe irritation, pain, burns
Response	Rinse cautiously with water for 30 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing.
	Immediately call a POISON CENTER/doctor.

Section continued on the next page

Page 4 of 16



832FX-B

(PART B)

IF ON SKIN (or hair)	P303 + P361+ P353, P310, P363, P333 + P313
Immediate or Delayed Symptoms	redness, irritation, rash (allergic contact dermatitis), pain, chemical burns, blistering
Response	Take off immediately all contaminated clothing. Wash with plenty of water [shower].
	Immediately call a POISON CENTRE/doctor.
	Wash contaminated clothing before reuse.
	If skin irritation or rash occurs: Get medical advice/attention.
IF SWALLOWED	P301 + P330 + P331, P310
Immediate Symptoms	<i>irritation, abdominal pain, nausea, vomiting, burns to the digestive tract</i>
Response	Rinse mouth. Do not induce vomiting.
	Immediately call a POISON CENTER/doctor.
IF INHALED	P304 + P340, P310
Immediate Symptoms	cough, irritation of the respiratory track, burning sensation
Delayed Symptoms	asthma, difficulty breathing
Response	Remove person to fresh air and keep comfortable for breathing.
	Immediately call a POISON CENTER/doctor.

Advice to Physicians

In case of exposure to nitrogen oxides (NO_x) combustion products during a fire, the symptoms may be delayed. For significant exposures, the exposed person should be kept under medical surveillance for 48 hours.

Page **5** of **16**



(PART B)

Section 5: Fire-Fighting Measures		
Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.	
Specific Hazards	Not flammable or combustible, but burns if involved in a fire. Produces irritating and toxic fumes in fires or in contact with hot surfaces.	
	Toxic for aquatic environment: Prevent fire-fighting wash from entering waterway or sewer system.	
Combustion Products	Produces carbon oxides (CO, CO ₂) and nitrogen oxides (NO _x).	
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.	

Section 6: Accidental Release Measures

Personal Protection	Use personal protection recommended in Section 8.
Precautions for Response	Do not breathe fumes/mist/vapors.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways. Do not flush to sewer.
Containment Methods	Contain with inert absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wipe residue with a paper towel wetted with a suitable organic solvent such as alcohol or ethyl lactate, and place dirty towels in container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose spill waste according to Section 13.

Page 6 of 16



832FX-B

(PART B)

Section 7: Handling and Storage		
Prevention	Keep out of reach of children.	
	Do not breathe fumes/mist/vapors.	
	Contaminated work clothing should not be allowed out of the workplace.	
	Do not eat, drink, or smoke when using this product.	
	Avoid release to the environment.	
Handling	Wear protective gloves/protective clothing/eye protection/face protection.	
	Wash contaminated clothing before reuse.	
	Wash hands thoroughly after handling.	
	Collect spillage.	
Storage	Store locked up.	

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

This product contains no substances with occupational exposure limits.

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Due to low vapor pressure of the product, general ventilation should be adequate for normal use. If the product is heated at high temperatures or worker is allergic, use local ventilation and consider using a full mask with organic vapor cartridges.

Section continued on the next page

Page **7** of **16**



(PART B)

Personal Protective Equipment

Eye protection	Wear appropriate protective eyeglasses or chemical safety goggles.
	RECOMMENDATION: Use safety glasses with lateral protection (side shields).
Skin Protection	For likely contacts, use of protective butyl rubber, neoprene, or other chemically resistant gloves.
	For incidental contacts, use nitrile or other chemically resistant gloves.
Respiratory Protection	For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.
	Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.
	If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.
	RECOMMENDATION: Consult your local safety supply store to ensure your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in section 3 of this SDS, and that the respirator is fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Page 8 of 16



832FX-B

(PART B)

Section 9: Phys	ical and Chemic	al Properties
-----------------	-----------------	---------------

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Clear, amber	Upper Flammability Limit	Not available
Odor	Ammonia-like	Vapor Pressure @20 °C ^{b)}	0.02 hPa [0.02 mmHg]
Odor Threshold	Not available	Vapor Density	Not available
рН	Not available	Relative Density @25 °C	0.98
Freezing/Melting Point	Not available	Solubility in Water	Slightly soluble
Initial Boiling Point ^{a)}	>230 °C [>446 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{b)}	>104 °C [>219 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Not available	Viscosity @25 °C	165 cP

a) Component with the lowest closed cup value—2,4,6-tris(dimethylaminomethyl)phenol b) Literature value for trimethylhexamethylenediamine

Section 10: Stability and Reactivity

Reactivity	Reacts exothermically with epoxides.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to	Avoid excessive heat and incompatible substances.
Avoid	Do not use in a way that forms a mist or aerosolize the product.
Incompatibilities	Strong oxidizing agents, strong acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.



(PART B)

Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes	May causes redness, severe eye irritation, pain, or burns.
Skin	May cause redness, serious skin irritation, allergic contact dermatitis, pain, chemical burns, or blistering.
Inhalation	Inhalation of vapors or mist may cause irritation to the nose, throat and lung (upper respiratory tract).
Ingestion	May cause irritation, abdominal pain, nausea, vomiting, burns to the digestive tract. May cause allergic reactions (see inhalation symptoms).
Chronic	Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
polyoxypropylene diamine	480 mg/kg ^{a)} Rat	2 090 mg/kg ^{a)} Rabbit	Not established
phenol, styrenated	3 700 mg/kg	>5 010 mg/kg	>4.9 mg/L
	Rat ^{a)}	Rabbit ^{a)}	(mist) Rat ^{a)}
amines, coco alkyl	1 300 mg/kg	>2 000 mg/kg	Not
	Rat ^{a)}	Rat ^{a)}	available
trimethylhexamethylenediamine	Not	Not	Not
	available	available	available
2,4,6-tris(dimethylaminomethyl)	Not	Not	Not
phenol	available	available	available

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier SDS were also consulted.

a) Supplier MSDS

Section continued on the next page

Page **10** of **16**



832FX-B

(PART B)

Other Toxicological Effects	
Skin corrosion/irritation	The hardener system causes skin burns.
Serious eye damage/irritation	The hardener system causes severe eye damage.
Respiratory and skin sensitization (allergic reactions)	Trimethylhexamethylenediamine and 2,4,6- tris(dimethylaminomethyl)phenol may cause skin sensitization according to animal studies.
Carcinogenicity (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Long term or repeated exposure to "amines, coco alkyl" are believed to lead to liver damage and immune system deficiencies.
Aspiration hazard	Based on available data, the classification criteria are not met. Contains $<10\%$ category 1 components, and the kinematic viscosity is >20.5 mm ² /s at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<u>http://echa.europa.eu</u>), and other reliable sources.

The coco alkyl amines is classified as a chronic category 1 environmental toxicant with an M-factor of 10.

The phenol, styrenated compound is classified as chronic category 2 environmental toxicants.

The trimethylhexamethylenediamine and 2,4,6-tris(dimethylaminomethyl)phenol compounds are classified as chronic category 3 environmental toxicants.

Section continued on the next page

Page **11** of **16**



(PART B)

Acute Ecotoxicity

Category 1 Very toxic to aquatic life

Chronic Ecotoxicity

Category 1

Very toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not readily biodegradable

Bioaccumulation

Not available

Other Effects

Not available


Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**



Section continued on the next page

Page **12** of **16**



832FX-B

(PART B)

Air

Refer to ICAO-IATA Dangerous (Goods Regulations.
Sizes 0.5 L and under Limited Quantity	Sizes greater than 0.5 L up to 1 L UN number: UN2735 Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (trimethylhexamethylenediamines, polyolxypropylene diamine) Class: 8 Packing Group: II Marine Pollutant: Yes
Excepted E2 ≤30 mL Quantity	

Sea

Refer to IMDG regulations.		
Sizes 1 L and under Limited Quantity	Sizes greater than 1 L UN number: UN2735 Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (trimethylhexamethylenediamines, polyolxypropylene diamine) Class: 8 Packing Group: II Marine Pollutant: Yes	

Note: Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.

Page **13** of **16**



(PART B)

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA

Other Classifications

HMIS® RATING

HEALTH:	* 3
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product does not contain substances that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any listed substances in California.

Section continued on the next page

Page 14 of 16



(PART B)

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information	
-------------------------------	--

SDS Prepared by	MG Chemicals' Regulatory Department
Date of Revision	10 August 2022
Supersedes	28 February 2020
Reason for Changes:	Minor modifications.

Reference

1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

- ACGIH American Conference of Governmental Industrial Hygienists (USA)
- EC50 Half maximal effective concentration
- EL50 Half maximal effective loading
- IARC International Agency for Research on Cancer
- NOELR No observable effect loading ratio
- NTP National Toxicology Program
- GHS Globally Harmonized System of Classification of Labeling of Chemicals
- LC50 Lethal Concentration 50%
- LCLo Lowest published lethal concentration
- LD50 Lethal Dose 50%
- OEL Occupational Exposure Limit
- PEL Permissible Exposure Limit
- SDS Safety Data Sheet
- STEL Short-Term Exposure Limit
- TCLo Lowest published toxic concentration
- TWA Time Weighted Average
- VOC Volatile Organic Content

Section continued on the next page

Page **15** of **16**



(PART B)

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at <u>www.mgchemicals.com</u>.

Email: support@mgchemicals.com

Mailing Addresses Manufacturing & Support 1210 Corporate Drive Burlington, Ontario, Canada L7L 5R6

Disclaimer This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.

Page **16** of **16**