т <u>Ω</u> "	m	1	0	Ξ	A	
			LAYOUT SHO	WN AS EXAMPLE		
Keying Shown as example						
CHARACTERISTICS Conner -Standard : Based on MIL-DTL-38999 Series III Dim	ctor dimension					
-Shell Material : Aluminium ØS -Shell Plating : Black Zinc Nickel Z -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum	21.8 Max 31 Max		due to a use of the Proo the Specifications issued by		with hird party	
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D	509Z98PN		
-Temperature Range: -65°C to +175°C-Salt Spray: 500 hours-Mass: 11.47 g ± 10%		A 15-10-2016 Fir ISS DATE Designed By:	st Release Latest modification - by Date:	CU	STOMER DRAWING	MOD N°
		TITLE	A	Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 09 Z 98 P N SHELL TYPE : Plug with RFI Shielding - - 09 Z 98 P N		SCALE	General Tolera ±-	inces:	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 09	ORIENTATION : N CONTACT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURI		This document is the proper SOURIAU it must not be reproduced communicated without perm	lor
PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 09-98	FORMAT A3		RIAU DRG N° 609Z98PN-C		SHEET 1/2
H G F	E D		<u> </u>	B		

		۵	н г	m	U	0	
		Contact Layout					
4	-X	$ \begin{array}{c} $					
	Shell Arrangement Numb size no. conta 9 -98 3	+ 065 (1.65) + 038 (0.97) + 000 (0.00) - 075 (1.91) - 065 (1.65) + 038 (0.97) - 065 (1.65) + 038 (0.97) - 065 (1.65) + 038 (0.97)					
ى ى							
	L						
						SOURIAU shall not be liable for due to a use of the Products the Specifications issued by eithe (professional recomment	w er c
N						PN: 8D50	
					A 15-10-20 ISS DATE Designed By:	16 First Release	
					SCALE	Alum General linea	
<u> </u>					NA	Tolerances:	
					FORMAT	U WWW.SOURIAU SOURIA	
		1	1		A3	8D509	
	Н	G	F	E	D	C	

