



- NOTES
- 1 ONE EXAMPLE OF THE ROTATION OF REF. ⑧, ⑨ TO REF. NO. ① IS SHOWN.
 - 2 THE RECOMMENDED TIGHTENING TORQUE OF REF. NO. ⑧ SHALL BE 3 TO 4 N · m.
 LOCTITE 243, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. ⑧ FROM LOOSENING.
 - 3 THE RECOMMENDED TIGHTENING TORQUE OF REF. NO. ⑫ SHALL BE 0.2 TO 0.3 N · m.
 LOCTITE 243, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. ⑫ FROM LOOSENING.
 ACROSS FLATS HEXAGON HEAD OF REF. NO. ⑫ : 1.27.
 - 4 THIS PRODUCTS TO BE USED WITH CABLE CLAMP, JR13WCC-*(72).
 *DESIGNATE DIAMETER(mm) OF APPLICABLE CABLE.
 - 5 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER,
 DEPENDING ON THE CABLE STRUCTURE, PLEASE CONFIRM BEFORE THE USE.

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
6	BRASS	NICKEL PLATING	12	STAINLESS STEEL	HEXAGON SOCKET SET SCREW M2.6×0.45×2
5	ACRYLONITRILE BUTADIENE RUBBER	(GRAY)	11	POLYACETAL	(WHITE)
4	DIALLYL PHTHALATE	(BLACK) UL94V-0	10	ACRYLONITRILE BUTADIENE RUBBER	(GRAY)
3	DIALLYL PHTHALATE	(BLACK) UL94V-0	9	BRASS	NICKEL PLATING
2	COPPER ALLOY	SILVER PLATING 5 μm min.	8	BRASS	NICKEL PLATING
1	BRASS	NICKEL PLATING	7	PHOSPHOR BRONZE	NICKEL PLATING

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△	APPROVED : HY. KOBAYASHI 18.02.22			
			CHECKED : HY. KOBAYASHI 18.02.22			
			DESIGNED : HY. KISHI 18.02.21			
			DRAWN : MK. INOUE 18.02.07			

DRAWING NO.	EDC-113483-31-00
PART NO.	RM15WTL P-10S(31)
CODE NO.	CL109-0999-4-31