



TO SNAP-LOCK IN A $.187 \pm .003$
 (4.75 ± 0.08) DIA. HOLE, IN A
 $1/16$ TO $9/64$ $(1.6$ TO $3.6)$ THICK PANEL.

NOTES:

1. MATERIAL: NYLON 6/6 (RMS-01), NATURAL.
 UV STABILIZED NYLON (RMS-46), BLACK.
 BY SPECIAL ORDER.
 FLAME RETARDANT NYLON (RMS-19), NATURAL.
 BY SPECIAL ORDER.
2. MIN. LOOP TENSILE: 18 LBS (80 NEWTONS).
3. MAX. BUNDLE DIAMETER: $3/4$ (19.1).

F	CHANGE FROM RMS-75 TO -19, ECN 1371	DZ 08.16.12	TITLE: SELF MOUNT WRAP-IT-TIES					DWG IN	
E	SEE CO 200134 FOR CHANGES	SK 02.28.08						IN (MM)	
D	SEE ECN #565 FOR CHANGES	SM 01.23.03	TOLERANCES UNLESS NOTED	FILE # WIT-18R2A	DWN: S.M.	APP:	FINAL		
C	COMPLETELY RE-DRAWN; NEW NOTES AND CHANGED FILE NO.	SM 03.15.01	.XX=±.010	MAT'L: SEE NOTES	DT: 03/15/01	DT:	PART #	PRINT TYPE	
B	DIM $(4.75 \pm .08)$ WAS $(4.75 \pm .8)$	JL 6/10/99	.XXX=±.005	RE: RICHCO, INC.	RICHCO INC. PO BOX 804238, CHICAGO, 60680		WIT-18R2A-4-01	CA	
A	REMOVED TABLE & CORRECTED PART#	AM 5/6/99	FRAC=±1/64			(773) 539-4060			
REV	DESCRIPTION	ENGR DATE	ANG=1°						