


RAD-PIG-EF316-MCX-SMA

Order No.: 2867678

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2867678>

Adapter cable, pigtail 100 cm MCX (male) -> SMA (male), insertion
attenuation 1.5 dB at 2.4 GHz; impedance 50 ohms;

Commercial data

| | |
|--------------------------|---|
| GTIN (EAN) |  4 017918 939045 |
| sales group | H178 |
| Pack | 1 pcs. |
| Customs tariff | 85442000 |
| Catalog page information | Page 547 (IF-2009) |

Product notes

WEEE/RoHS-compliant since:
09/02/2008



[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Technical data

General

| | |
|--------------------|---------------------------|
| Connection 1 | Plug connector connection |
| Type of connection | Typ MCX (male) |
| Connection 2 | Plug connector connection |
| Type of connection | Type SMA (male) |
| Fixed cable length | 100 cm |

| | |
|---------------------------------|---------------------------|
| Cable type | EF 316 |
| Cable, attenuation | approx. 1.5 dB/m |
| Minimum bending radius | 12.50 mm |
| External diameter | 2.50 mm |
| Outer sheath, material | Radox (LSFH) |
| Connection name | Plug connector connection |
| Type of connection | Typ MCX (male) |
| Ambient temperature (operation) | -40 °C ... 70 °C |

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;