

## Specification Sheet

Part Number: T50R0UVC2



UV Resistant Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66UV, Black, 100/pkg

Article Number	112-05060
Type	T50R
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Engineered and manufactured for maximum performance and quality.</li><li>• Made from 100% high-quality plastic to ensure efficient recycling.</li><li>• Inside serration for a strong hold onto bundles.</li><li>• Easy application either manually or with a tensioning tool.</li><li>• Bent tail allows for simpler insertion.</li></ul>
Quantity Per	bag

### Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	UV Resistant Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66UV, Black, 100/pkg
<b>Global Part Name</b>	T50R-PA66UV-BK
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	8.0
<b>Length L (Metric)</b>	202.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	1.97
<b>Bundle Diameter Max (Metric)</b>	50.0

<b>Thickness T (Imperial)</b>	0.05
-------------------------------	------

<b>Thickness T (Metric)</b>	1.2
-----------------------------	-----

<b>Material</b>	Polyamide 6.6 UV-resistant (PA66UV)
-----------------	-------------------------------------

<b>Material Shortcut</b>	PA66UV
--------------------------	--------

<b>US MIL SPEC</b>	MS3367-1-0
--------------------	------------

SAE-AS33671	<b>Flammability</b>
-------------	---------------------

UL 94 V2	<b>Halogen free</b>
----------	---------------------

Yes	<b>Operating Temperature (Metric)</b>
-----	---------------------------------------

-40°F to +185°F (-40°C to +85°C)	<b>Reach Complaint(Article 33)</b>
----------------------------------	------------------------------------

Yes	<b>ROHS Complaint</b>
-----	-----------------------

Yes	<b>Certification/Specification WEB</b>
-----	--

CAGE Code 53421 UL-ZODZ2.E64139 BACS38K	<b>UL Recognized (US)</b>
---	---------------------------

Yes	<b>UL Recognized (US and Canada)</b>
-----	--------------------------------------

Yes	
-----	--

<b>Package Quantity(Imperial)</b>	100
-----------------------------------	-----

**Package Quantity (Metric)** 100

**Customs Number** 3926909987

**Content Unit(BMEcat)** pcs.

**Weight (Metric)** 1.3