

## Specification Sheet

Part Number: T50R2C2UL



Standard Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 100/pkg

Article Number	111-00514
Type	T50R
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none"><li>• Inside serrations allow for strong hold on cables and wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force.</li><li>• Bent tail ensures a quick and simple installation.</li></ul>
Quantity Per	bag

### Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description**

Standard Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 100/pkg

**Global Part Name**

T50R-PA66-RD

**Minimum Tensile Strength (Imperial)**

50.0

**Minimum Tensile Strength (Metric)**

225.0

**Length L (Imperial)**

8.0

**Length L (Metric)**

202.0

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.18

**Width W (Metric)**

4.6

**Bundle Diameter Min (Imperial)**

0.06

**Bundle Diameter Min (Metric)**

1.5

**Bundle Diameter Max (Imperial)**

1.97

**Bundle Diameter Max (Metric)**

50.0

<b>Thickness T (Metric)</b>	1.2
-----------------------------	-----

<b>Material</b>	Polyamide 6.6 (PA66)
-----------------	----------------------

<b>Material Shortcut</b>	PA66
--------------------------	------

<b>US MIL SPEC</b>	SAE-AS33671
--------------------	-------------

<b>MS3367-1-2</b>	
<b>Flammability</b>	

UL 94 V2	<b>Halogen free</b>
----------	---------------------

Yes	<b>Operating Temperature (Metric)</b>
-----	---------------------------------------

-40°F to +185°F (-40°C to +85°C)	<b>ROHS Complaint</b>
----------------------------------	-----------------------

Yes	<b>Certification/Specification WEB</b>
-----	--

UL-ZODZ.E64139 CAGE Code 53421	<b>UL Recognized (US)</b>
--------------------------------	---------------------------

Yes	<b>UL Listed (US and Canada)</b>
-----	----------------------------------

Yes	<b>UL Recognized (US and Canada)</b>
-----	--------------------------------------

Yes	
-----	--

<b>Package Quantity(Imperial)</b>	100
-----------------------------------	-----

<b>Package Quantity (Metric)</b>	100
----------------------------------	-----

**Customs Number**

3926909987

---

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)