




Specialty Terminals

10-2-WN thru 10-10-WN
Ring Tongue, Nylon Insulated



Data Sheet

3M™ Product Number	Wire Range (AWG)	Stud Size	W	E	Thickness	Barrel I.D.	Maximum Insulation Diameter
10-2-WN	26-22	2	0.19	0.55	0.20	0.35	0.09
10-4-WN	26-22	4	0.19	0.55	0.20	0.35	0.09
10-6-WN	26-22	6	0.24	0.63	0.20	0.35	0.09
10-8-WN	26-22	8	0.25	0.63	0.20	0.35	0.09
10-10-WN	26-22	10	0.31	0.63	0.20	0.35	0.09

Specifications

Wire Size:	See Table Above
Barrel Seam:	Brazed
Max. Voltage Rating:	600 V Building Wire 1000 V Signs, Fixtures and Luminaires
Max. Operating Temp.:	221°F (105°C)
Max. Current:	Same as Wire
Insulator Material:	Nylon
Terminal Material:	Copper
Plating:	Tin


Installation Information

WARNING

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

Strip away the end 3/8 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M Scotchlok Crimping Tool TH-450.



Barrel Crimp (Electrical)

Engineering Specification

Crimp-type terminals shall, electrically and mechanically, connect to a pre-stripped end of a stranded copper wire and have a flat tongue portion with a central opening for mounting around a screw or stud.

The terminal line shall offer tongue variations in hole (stud) size (6, 8 10, etc.) and configuration (ring, fork, block fork, flanged block fork, locking fork, etc.): and barrel variations in wire (AWG) size (24, 22-18, 16-14, 12-10, etc.) and construction (non-insulated brazed seam, vinyl insulated butted seam, nylon insulated with insulation grip, etc.).

The nylon-insulated, ring tongue terminal shall be tin-plated, annealed copper, with the tongue having a specified stud hole (size 2 thru 10) and a brazed seam barrel, covered by a molded nylon sleeve, color coded and sized for 26-22 (AWG) wire.

3M and Scotchlok are trademarks of 3M Company.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of five (5) years from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



Electrical Markets Division

6801 River Place Blvd.
Austin, TX 78726-9000
800-245-3573
Fax 800-245-0329
www.3M.com/electrical

Please recycle. Printed in USA.
© 3M 2007. All rights reserved.
78-8131-7367-7-A