



General ordering data

Order No.	0354760000
Part designation	EK 35
Version	Earth terminal, 35 mm ² , Screw connection, PA 66, green/yellow, TS 32
EAN	4008190187972
Qty.	20 pc(s).

Product notes

Note, accessories	The TS 35/15 Cu must be used when connecting conductors of 50 mm ² .
-------------------	---

PT OKIECEEx/ATEX rating data

EU-type examination certificate	KEMA97ATEX1798U
Download, German	KEMA97ATEX1798U_d.pdf
Download English	KEMA97ATEX1798U_e.pdf
IECEX Certificate of Conformity	IECEXKEM06.0014U
ATEX conductor cross-section	35 mm ²
IECEX conductor cross-section	35 mm ²
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	Einsatztemperaturbereich siehe EG-Baumusterprüfbescheinigung/IECEX-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

Additional technical data

Colour of insulating material	green/yellow
Connection direction	on side
End plate required	No
Explosion-tested version "Ex e"	Yes
Installation advice	TS 32
Insulating material	PA 66
Levels cross-connected internally	No
No. of identical terminals	1

Additional technical data

No. of levels	1
No. of terminal strips per level	2
Open sides	closed
Operating temperature range	- 50 °C, + 100 °C
Product family	SAK Series
Type of connection	Screw connection
Type of mounting	Screwed
UL 94 flammability rating of insulation material	V2
Version	PE terminal

CSA rating data

Min. cross-section (CSA)	AWG 10
Max. cross-section (CSA)	AWG 2

Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1)	10 mm ²
Flexible with ferrule, max. (DIN 46228 pt 1)	35 mm ²

Conductors for clamping (rated connection)

Clamping range, min.	6 mm ²
Clamping range, max.	50 mm ²
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	2
Stripping length	20 mm
Clamping screw	M 6
Blade size	6.5 x 1.0 mm
Tightening torque range	4.0...6.0 Nm
Gauge to IEC 60947-1	B9
Solid, min.	6 mm ²
Solid, max.	16 mm ²
Stranded, min.	16 mm ²
Stranded, max.	50 mm ²
Flexible, min.	10 mm ²
Flexible, max.	35 mm ²
Flexible with ferrule, min. (DIN 46228/1)	10 mm ²
Flexible with ferrule, max. (DIN 46228/1)	35 mm ²
AWG conductor size, min.	AWG 8
AWG conductor size, max.	AWG 2
AWG conductor size, min.	8.37 mm ²
AWG conductor size, max.	33.62 mm ²

Dimensions

Width	16 mm
Height of lowest version	67.5 mm
Length	58 mm
Weight	99.35 g
TS 35 offset	29 mm

PE rating data

Centre screw on PE terminals	M 3.5
PEN function	Yes
Pollution severity	3
Rated cross-section	35 mm ²
Rated impulse withstand voltage to adjacent terminal	8 kV
Rated short-time current	4200 A (35 mm ²)
Rated voltage for adjacent terminal	800 V
Standards	IEC 60947-7-2
Tightening torque range for fixing screw	0.8...1.6 Nm

Rating data

Rated cross-section	35 mm ²
Standards	IEC 60947-7-2
Pollution severity	3

UL rating data

Min. cross-section (UL)	AWG 6
Max. cross-section (UL)	AWG 2

Approvals

Approvals institutes



Classifications

ETIM 2.0	EC000901
ETIM 3.0	EC000901
eClass 4.1	27-14-03-05
eClass 5.0	27-14-03-05
eClass 5.1	27-14-03-05

Similar products

Order No.	Part designation	Version
0354660000	EK 10	Earth terminal, 10 mm ² , Screw connection, PA 66, green/yellow, TS 32
0374660000	EK 16	Earth terminal, 16 mm ² , Screw connection, PA 66, green/yellow, TS 32
0323100000	EK 2	Earth terminal, 10 mm ² , Screw connection, PA 66, TS 32
0474360000	EK 2.5N	Earth terminal, 2.5 mm ² , Screw connection, Polyamide, green/yellow, TS 32

0354560000	EK 4	Earth terminal, 4 mm ² , Screw connection, PA 66, green/yellow, TS 32
0144400000	SAKE 35	Earth terminal, 35 mm ² , Screw connection, TS 32
0213200000	SAKE 70/32	Earth terminal, 70 mm ² , Screw connection, TS 32