

SmartOnline Expandable 3U Rack / Tower UPS System - NAFTA assembled version of SU3000RTXL3U

MODEL NUMBER: **SU3000RMNAFTA**

Description

3000VA on-line, double-conversion UPS system for critical server, network and telecommunications equipment/3U rackmount form factor with an installed depth of 26 inches/Expandable battery runtime with optional BP72V28-3UNAFTA external battery packs/Full time sine wave 110 or 120V +/-2% output/Uninterruptible Power Supply (UPS) actively converts raw incoming AC power to DC, then re-converts output back to completely regulated, filtered AC output/Operates continuously without using battery power during brownouts to 65V and overvoltages to 138V/NEMA L5-30P input plug/NEMA 5-15, NEMA 5-15/20R and NEMA L5-30R output receptacles/Network-grade AC surge and noise suppression/Zero transfer time between AC and battery operation/Network management interfaces support simultaneous communications via USB port, DB9 serial port and SNMPWEBCARD slot/Includes USB and DB9 serial ports. Built-in DB9 port offers both enhanced RS-232 enabled monitoring data, plus contact closure monitoring ability. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X/Supports simultaneous detailed monitoring of equipment load levels, self-test data and mains power conditions via all 3 network interfaces at once/Includes PowerAlert monitoring software and complete cabling/Emergency Power Off (EPO) interface/Integrated two bank PDU switching supports load shedding and remote-reboot of connected equipment/3 stage metered current monitoring and battery charge status LEDs/Dataline surge suppression for dialup, DSL or network ethernet connection/Mains power and voltage regulation LEDs/Audible Alarm/Self-test/Fault-tolerant auto-bypass mode/LED display panel easily rotates for better viewing in rackmount or tower configurations/4 post rackmount accessories/2-9USTAND tower kit and 2POSTRMKITWM two post rackmount hardware accessories available/Field replaceable, hot swappable internal batteries and external battery packs/Attractive all-black UPS design/Two year warranty with \$250,000 connected equipment insur/Extended warranty and service contracts available

Features

- SmartOnline high performance UPS system is ideal for critical voice, data, medical and industrial network applications
- True on-line, double-conversion UPS provides perfectly regulated sine wave output within 2% of 110/120V (user selectable) under all usage conditions
- Maintains continuous operation through blackouts, voltage fluctuations and surges with zero transfer time
- Removes harmonic distortion, fast electrical impulses, frequency variations and other hard to solve power problems not addressed by other UPS types
- Corrects line voltage conditions as low as 65V and as high as 138V back to selectable 110/120V (+/-2%) values
- Standard internal battery set offers 17 minutes runtime at half load (1200W) and 6 minutes at full load (2400W)
- Optional BP72V28-3UNAFTA external battery pack increases runtime to 78 minutes at half load (1200W) and 34 minutes at full load (2400W/multi-pack compatible)
- Compact rackmount form factor installs using only 3 rack spaces (3U) with a maximum installed depth of 26 inches
- Ships with all mounting accessories for 4 post rackmount installation
- Optional 2POSTRMKITWM enables 2 post rackmount installation

Highlights

- 3000VA / 2400W on-line, double-conversion, extended-run 3U rack / tower UPS
- Maintains sine-wave 110/120V +/-2% output during overvoltages to 138 and brownouts as low as 65V (50/60Hz auto-sensing)
- Simultaneous use communications via HID compliant USB port, serial port, SNMP/Web card slot and EPO interface
- Fault tolerant auto-bypass mode, current monitoring and switched PDU control via 2 switchable output load banks
- Input: NEMA L5-30P (120V) / Output: 4 NEMA5-15R, 4 NEMA5-15/20R & 1 NEMA L5-30R
- 2 year product warranty / \$250,000 Ultimate Lifetime Insurance (USA & Canada only)

Package Includes

- SU3000RMNAFTA UPS System
- PowerAlert Software and Cabling
- Mounting hardware for 4 post rack enclosures
- Instruction manual with warranty information



- Optional 2-9U STAND accessory enables small-footprint upright tower placement
- Fault tolerant auto-bypass maintains continuous utility output to connected equipment, even in cases where the UPS suffers internal failure and requires maintenance
- Network interfaces support simultaneous communications via built-in USB, DB9 serial/contact-closure and SNMP WEBCARD slot
- HID compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X.
- Included PowerAlert UPS monitoring software supports safe unattended shutdown, monitoring and control via local connected servers, plus any number of additional servers over IP
- UPS interface supports on-battery, low-battery, power-restored, AC-voltage, DC-voltage, output current monitoring, battery charge current, battery capacity, AC line frequency, timed inverter shutoff, activate self-test, load bank output power control and remote reboot, UPS nominal voltage adjustment and UPS line to battery power voltage setpoints
- Built-in Emergency Power Off (EPO) interface with cable
- NEMA L5-30P input plug/NEMA 5-15/20R, L5-20R & L5-30R output receptacles
- Integrated 2 bank switched PDU enables remote outlet management for load shedding or remote reboot of individual load banks (each bank has four outlets)
- Front panel LEDs offer current monitoring and battery charge level information
- UPS ships fully assembled in full compliance with DOT regulations; no time consuming connection of internal batteries by user required
- Single line TEL/DSL or network ethernet line surge suppression
- 2 year manufacturer's product warranty; \$250,000 Ultimate Lifetime Insurance

Specifications

| OVERVIEW | |
|-----------------------------|---|
| UPC Code | 037332137661 |
| OUTPUT | |
| Frequency Compatibility | 50 / 60 Hz |
| Output (VA) | 3000 |
| Output (Watts) | 2400 |
| Output Nominal Voltage | 120V AC (100/110/120V) |
| Output Voltage Regulation | Maintains full-time sine wave output within 2% of selected nominal, less than 3% total harmonic distortion (linear load) / 5% total harmonic distortion (computer load) (Less than 5% THD on-line and on-battery) |
| Output Frequency Regulation | Regulates line frequency to 50/60Hz +/- 0.05Hz |
| Overload Protection | Via 40A input breaker |



| | |
|--|--|
| Customized Load Management Receptacles | 2 controllable load banks support load shedding and remote reboot on demand of locked network devices (each bank has 4 outlets) |
| INPUT | |
| UPS Input Cord Length (ft.) | 10 |
| UPS Input Cord Length (m) | 3.1 |
| Recommended Electrical Service | 120V 30A dedicated circuit |
| Maximum Input Amps | 24 |
| Input Connection Type | NEMA L5-30P |
| Voltage Compatibility (VAC) | 100; 110; 120 |
| BATTERY | |
| Full Load Runtime (min.) | 6 minutes (2400 watts) - add 1 battery pack for 17 minutes, or add 1 BP72V28-3UNAFTA for 34 minutes |
| Half Load Runtime (min.) | 17 minutes (1200 watts) - add 1 battery pack for 39 minutes, or add 1 BP72V28-3UNAFTA for 78 minutes |
| Expandable Battery Runtime | Supports extended runtime with optional external battery packs BP72V28-3UNAFTA for 34 minutes, or add 1 BP72V28-3UNAFTA for 78 minutes (multi-pack compatible) |
| DC System Voltage (VDC) | 72 |
| Battery Access | User replaceable, hot-swappable battery replacement supported via front access panel |
| Battery Pack Accessory (Optional) | BP72V28-3UNAFTA (multi-pack compatible) |
| Replacement Battery Cartridge | RBC96-3U (qty 1) |
| Typical Battery Lifespan | 3-6 years, depending on usage |
| Battery Charge | less than 6 hours to 80% |
| VOLTAGE REGULATION | |
| Voltage Regulation Description | On-line, double-conversion power conditioning maintains output within 2% of 110/120 volts at all times |
| Overvoltage Correction | Maintains output of selected nominal +/-2% during overvoltages to 138V AC |
| Brownout Correction | Maintains output of selected nominal +/-2% during undervoltages to 65V AC (at loads greater than 70% undervoltage correction extends to 80V) |
| USER INTERFACE, ALERTS & CONTROLS | |
| Front Panel LEDs | LED STATUS DISPLAY: line power (green), online (green), bypass (yellow), on battery (green), overload (red), battery low (yellow) - 4 LED LOAD / BATTERY LEVEL DISPLAY (100%, 75%, 50%, 25%). LED display panel easily rotates for better viewing in rackmount or tower configurations. |
| Switches | Includes power off/on switch to enable system turn on (press ON switch), UPS battery test (press ON switch during normal AC operation), buzzer silence (press ON switch during battery operation) and OFF (press OFF switch). All switch functions require that the switch be pressed and held for longer than 2 seconds, but less than 4 seconds |
| Audible Alarm | Multi-function audible alarm with distinctive ring patterns offer notification of backup operation (2 seconds on / 0.5 seconds off), low battery warning (1.25 seconds on / 0.5 seconds off), overload (sounds continuously), UPS fault (4.2 seconds on / 1 second off), input voltage out of frequency (2.1 seconds on / 0.14 seconds off) and high input voltage (2.1 seconds on / 0.07 seconds off) |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| SURGE / NOISE SUPPRESSION | |
|--|---|
| UPS AC Suppression Joule Rating | 480 |
| EMI / RFI AC Noise Suppression | Yes |
| AC Suppression Response Time | Instantaneous |
| Dataline Suppression | Set of 8 wire RJ style interface jacks offer surge suppression for network ethernet or TEL/DSL connection. Pins 1,2,3 and 6 offer ethernet protection starting at 7.5V and the center two wires, pins 4 & 5, offer TEL/DSL line suppression starting at 260V |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 11.25 x 23.00 x 31.50 |
| Shipping Dimensions (hwd / cm) | 28.58 x 58.42 x 80.01 |
| Shipping Weight (lbs.) | 112.44 |
| Shipping Weight (kg) | 51.00 |
| Unit Dimensions (hwd / in.) | 5.25 x 17.75 x 26 |
| Unit Dimensions (hwd / cm) | 13.3 x 45 x 66 |
| Unit Weight (lbs.) | 73.85 |
| Unit Weight (kg) | 33.50 |
| Cooling Method | Built-in cooling fan |
| Material of Construction | Steel |
| Form Factors Supported | Rack/Tower (3U) |
| ENVIRONMENTAL | |
| Relative Humidity | 0 to 95%, non-condensing |
| COMMUNICATIONS | |
| WatchDog Compatibility | Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment ideal for unattended kiosk applications |
| Network Monitoring Port | Includes USB and DB9 serial ports. Built-in DB9 port offers both enhanced RS-232 enabled monitoring data, plus contact closure monitoring ability. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. |
| EPO Port | Supports "Emergency Power Off" via set of dedicated built-in EPO jacks |
| SNMP Compatibility | Yes, includes slot for optional SNMPWEBCARD accessory (#SNMPWEBCARD) |
| LINE / BATTERY TRANSFER | |
| Transfer Time (Line Power to Battery Mode) | Zero, online UPS continuously converts incoming AC to DC, then back to AC. When commercial power is interrupted, UPS maintains continuous output from battery reserves with absolutely no disruption in output AC power. |
| Low Voltage Transfer to Battery Power | Maintains continuous operation during undervoltages as low as 65V (80V at load levels over 70%). Below this switchover point, output is supported from battery derived AC power. |



| | |
|--|--|
| High Voltage Transfer to Battery Power | Maintains continuous operation without using battery power during overvoltages to 138V. Above this point, output is supported from battery derived AC power. |
| SPECIAL FEATURES | |
| Cold Start | Yes, inverter can be "cold started" to enable temporary AC output during a power failure |
| CERTIFICATIONS | |
| Certifications | Tested to UL1778 (USA), CSA C22.2 No. 107.3 (Canada), NOM (Mexico), Class A (emissions), FCC Part 68 / Industry Canada (telecommunications), RoHS compliant |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |
| Optional Coverage | 3-5 year warranties, plus next day and on-site warranty coverage available for select opportunities. Contact Tripp Lite for additional information. |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$250,000 Ultimate Lifetime Insurance |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>