



| Model       | Length | Thread |
|-------------|--------|--------|
| <b>3263</b> | .50"   | 6-32   |
| <b>3264</b> | .50"   | 8-32   |
| <b>4511</b> | .63"   | 6-32   |
| <b>4512</b> | .63"   | 8-32   |

### FEATURES:

- Threaded stud for rapid mounting.
- Furnished with hex nut and tin plated solder lug.
- Ideal for connecting power supplies or test equipment to prototype circuit boards.
- Mates to Model #1581 or any standard banana jack.

Material: Copper per QQ-C-576.

Finish: Electro-tin plated.

Hex Nut, 8-32:

Material: Brass per QQ-B-626, Composition 22,  
½ Hard

Finish: Nickel plated.

### MATERIALS:

Banana plug:

Spring: Beryllium Copper, Berylco 25 per QQ-C-533, Cond. HT.

Plug Body: Brass per QQ-B-626, Alloy 360,

½ Hard Solder lug:

### RATINGS:

Working Voltage: 5000 VRMS

Current: 15 Amperes

### ORDERING INFORMATION: Model 3263

Parts are packaged ten per bag, unassembled.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Made in USA