

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MECHANICAL CHARACTERISTICS				
VIBRATION	FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES. 1	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. 1		X	-
ENVIRONMENTAL CHARACTERISTICS				
THERMAL SHOCK	TEMP -55 →+5 TO +35 →+85 →+5 TO +35 °C TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
CORROSION SALT MIST	EXPOSED AT 5 % SALT WATER, FOR 48 h.	NO HEAVY CORROSION THAT LOSE FUNCTION.	X	-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
1				
REMARK		APPROVED	AO. SUZUKI	11. 04. 11
1 EXAMINATION IS HELD WITH "DH80A- * * P".		CHECKED	KN. ICHIKAWA	11. 04. 11
Unless otherwise specified, refer to JIS C 5402 .		DESIGNED	MO. SHIMOYAMA	11. 04. 11
		DRAWN	MO. SHIMOYAMA	11. 04. 11
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-127363-00	
HRS	SPECIFICATION SHEET	PART NO.	DH80A-SCREW	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0059-4-00	1 / 1/1