

841AR-P

PEN

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: 841AR (Pen)**Other Means of Identification:** Nickel Conductive Pen**Related Part #** 841AR-P, 841AR-PCA

Recommended Use and Restriction on Use

Use: Electrically conductive coating and EMI/RFI shield**Uses Advised Against:** Not available

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA**☎** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**☎** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**

(Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

841AR-P
PEN
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria		Category	Signal Word	Pictograms
Flammable Liquid		2	Danger	Flame
Specific Target Organ Toxicity	Repeated Exposure	1	Danger	Health
Carcinogenicity		2	Warning	Health
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Specific Target Organ Toxicity	Single Exposure	3	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	3	<i>none</i>	<i>none</i>

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
	H372: Causes damages to organs (lungs) through prolonged or repeated exposure by inhalation H351: Suspected of causing cancer
	H317: May cause allergic skin reaction H319: Causes serious eye irritation H336: May cause drowsiness or dizziness
<i>none mandated</i>	H412: Harmful to aquatic life with long lasting effects

Section continued on the next page

841AR-P
PEN
Continued ...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P201, P202	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P260 + P271	Do not breathe vapors. Use only outdoors or in a well-ventilated area.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P308 + P313	IF exposed or concerned: Get medical advice or attention.
P303 + P361 + P364 + P352	IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of water [shower].
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
Storage	Precautionary Statements
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national international regulations.

Section continued on the next page

841AR-P
PEN
Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
7440-02-0	nickel	43%
616-38-6	dimethyl carbonate	14%
67-64-1	acetone	12%
110-43-0	heptan-2-one ^{a)}	9%
67-63-0	propan-2-ol	8%
123-86-4	n-butyl acetate	2%
108-65-6	1-methoxy-2-propanol acetate	1%

a) Also known as methyl amyl ketone (MAK)

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF ON SKIN (or hair)	P303 + P361 + P353, P333 + P313, P308 + P313, P363
Immediate Symptoms	<i>redness, mild irritation, dry skin</i>
Response	Take off immediately all contaminated clothing. Rinse skin with water [shower]. If skin irritation or rash occurs: Get medical advice or attention. IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse.

Section continued on the next page

841AR-P
PEN
Continued...

IF INHALED	P304 + P340, P312, P308 + P313
Immediate Symptoms	<i>cough, drowsiness, dizziness, headaches, nausea, unconsciousness</i>
Response	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell. IF exposed or concerned: Get medical advice or attention.
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>irritation, redness, pain</i>
Response	Rinse cautiously with water for 20 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
IF SWALLOWED	P301 + P330 + P331, P308 + P313
Immediate Symptoms	<i>nausea, sore throat, abdominal pain, diarrhea, drowsiness, dizziness</i>
Response	Rinse mouth. Do NOT induce vomiting. IF exposed or concerned: Get medical advice or attention.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
Specific Hazards	Produces irritating and toxic fumes in fires or in contact with hot surfaces. May produce very toxic nickel carbonyl gas in the presence of carbon monoxide in a reducing atmosphere. The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO,CO ₂), nickel oxides fumes, and nitrogen oxides (NO _x).
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Do not breathe the vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Not applicable
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe breathing vapors. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Do not eat, drink, or smoke when using this product.
Handling	Wear protective gloves. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands thoroughly after handling.
Storage	Avoid release to the environment. Collect spillage. Store in a well-ventilated place. Keep cool. Store locked up.

Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
nickel	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	1.5 mg/m ³ 1 mg/m ³ 1.5 mg/m ³ 0.05 mg/m ³ 1 mg/m ³ 1 mg/m ³	Not established Not established Not established Not established Not established Not established
acetone	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm 1 000 ppm 500 ppm 250 ppm 500 ppm 750 ppm	750 ppm Not established 750 ppm 500 ppm 750 ppm 1 000 ppm
heptan-2-one <i>methyl amyl ketone</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	50 ppm 100 ppm 50 ppm 50 ppm 25 ppm 50 ppm	Not established Not established Not established Not established Not established Not established
propan-2-ol	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	200 ppm (TWA) 400 ppm 200 ppm 200 ppm 200 ppm 400 ppm	400 ppm — 400 ppm 400 ppm 400 ppm 500 ppm
n-butyl acetate	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	150 ppm 150 ppm 150 ppm 20 ppm 150 ppm 150 ppm	Not established Not established 200 ppm 200 ppm Not established 200 ppm

Section continued on the next page

841AR-P
PEN
Continued...

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
1-methoxy-2-propanol acetate	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	50 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	50 ppm	75 ppm
	Canada ON	50 ppm	Not established
	Canada QC	Not established	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database² and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Engineering Controls

Ventilation Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Ensure that glasses have side shields for lateral protection.

Skin Protection For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

Respiratory Protection For over-exposures up to 10 x OEL of vapors, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit ^{b)}	2%
Appearance	Dark grey	Upper Flammability Limit ^{b)}	13%
Odor	Acetone-like	Vapor Pressure ^{b)} @20 °C	11 kPa [86 mmHg]
Odor Threshold ^{a)}	5 ppm	Vapor Density	≥2 (Air =1)
pH	Not available	Relative Density @25 °C	1.7
Freezing/Melting Point	Not available	Solubility in Water	Partially miscible
Initial Boiling Point ^{a)}	56 °C [132 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	-17 °C [1.4 °F]	Auto-ignition Temperature ^{c)}	≥315 °C [≥599 °F]
Evaporation Rate	Fast	Decomposition Temperature	Not available
Flammability	Highly Flammable	Viscosity @25 °C	1 460 cP

a) Values based on acetone component.

b) Lower and Upper Explosive Limits, and vapor pressure of mixture calculated using Le Chatelier principle and component physical values.

c) The auto-ignition value is based on 1-methoxy-2-propanol acetate, which is the component with the lowest value.

Section 10: Stability and Reactivity

Reactivity	The nickel can react vigorously with acids and liberate hydrogen, which can form an explosive mixture in air. Nickel may react with carbon monoxide in a reducing atmosphere to form a very toxic nickel carbonyl gas.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Ignition sources, open flames, excessive heat, and incompatible substances
Incompatibilities	Oxidizing agents, strong acids, acid anhydrides
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information**Summary of Effects and Symptoms by Routes of Exposure**

Eyes	Causes redness, severe irritation, and pain.
Inhalation	May cause cough, drowsiness, dizziness, headaches, nausea, or unconsciousness.
Ingestion	May cause nausea, sore throat, abdominal pain, and diarrhea (also see inhalation symptoms).
Skin	Causes skin redness, mild irritation, and dry skin.
Chronic	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin. Exposure to silver powder may also cause argyria, an irreversible blue-grey discoloration of the skin. Chronic inhalation exposure to nickel dust or mist may affect the central nervous system, damage lungs, and lead to hearing loss with co-exposure to loud noises.

Section continued on the next page

841AR-P
PEN
Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
nickel	5 000 mg/kg Rat	Not available	Not available
acetone	5 800 mg/kg Rat	20 mL/kg Rabbit ^{a)}	16 000 ppm 4 h Rat ^{a)}
dimethyl carbonate	>6.4 g/kg Rat & Mouse	>5 000 mg/kg Rabbit	Not available
isopropyl alcohol	3 600 mg/kg Rat	12 800 mg/kg Rabbit	16 000 ppm 8 h Rat
n-butyl acetate	>10 768 mg/kg Rat	>17 600 mg/kg Rabbit	390 ppm 4 h Rat
heptan-2-one	1 670 mg/kg Rat	12 600 µL/kg Rabbit	>16.7 mg/kg 4 h Rat (vapor)
1-methoxy-2-propanol acetate	8 532 mg/kg Rat	>5 g/kg Rabbit	Not available

Note: Toxicity data from the RTECS² and ECHA database were consulted. The data from supplier SDS were also consulted.

a) Supplier safety data sheet

Other Toxicological Effects

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Acetone is a known serious eye irritant. Contains mechanically abrasive particles.
Sensitization (allergic reactions)	Exposure to nickel may cause allergic skin reaction.

Section continued on the next page

841AR-P**PEN****Carcinogenicity**
(risk of cancer)

Nickel is classified as a suspect carcinogen based on animal intratracheal instillation (intubation) or interperitoneal (in body cavity) injection studies. A reliable 2008 study by Oller et al. shows no carcinogenicity for the nickel metal via normal inhalation route.

Nickel [7440-02-0]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A5: Not suspected as a human carcinogen

CA Prop 65: Listed as a carcinogen

NTP: Reasonably anticipated to be human carcinogen

Mutagenicity

(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

Reproductive Toxicity

(risk to sex functions)

Based on available data, the classification criteria are not met.

Teratogenicity

(risk of fetus malformation)

Based on available data, the classification criteria are not met.

STOT-single exposure

Inhalation of acetone, heptan-2-one, n-butyl acetate may affect the central nervous system.

STOT-repeated exposure

Inhalation of dust/mist nickel particles can damage the respiratory tract leading to inflammation, lung fibrosis, and accumulation of nickel particles in a rat study.

Aspiration hazard

Based on available data, the classification criteria are not met. There is less than 10% category 1 components.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Contains nickel of less than a 1 mm but more than 100 nm (larger than nanoparticles), which release ionic silver levels that are harmful to the environment. While massive nickel is insoluble in water, its powder is considered sufficiently soluble to give rise to an ecological hazard by EU regulators. The classification that follows takes into account to chronic aqueous toxicity of category 3 assignment of the EU.

The n-butyl acetate ingredient is an acute category 3 environmental toxicant liquid (biodegradable, with minimal LC50 of 18 mg/L for fathead minnow).

Acetone, heptan-2-one, 2-propanol, and 1-methoxy-2-propanol acetate are not classifiable as an environmental toxicant (with minimal LC50 of >100 mg/L).

- Acetone has a minimal LC50 96 h of 5 540 mg/L for *Oncorhynchus mykiss* (rainbow trout) and an EC50 48 h of 13 500 mg/L for *Daphnia magna* (water flea).
- Heptan-2-one has a minimal LC50 96 h of 126 mg/L for *Pimephales promelas* (fathead minnow).
- The 2-propanol has a minimal LC50 of 9 640 mg/L 96 h for *Pimephales promelas* (fathead minnow); 5 102 mg/L 24 h *Daphnia magna* (water flea); >2 000 mg/L 24 h *Pseudokirchneriella subcapitata* (green algae).
- 1-methoxy-2-propanol acetate has a minimal LC50 96 h of ≥ 100 mg/L *Salmo gairdneri* and an EC50 48 h of >500 mg/L for *Daphnia magna* (water flea).

There is insufficient data to classify dimethyl carbonate for aqueous toxicity.

Acute Ecotoxicity

See chronic ecotoxicity

Chronic Ecotoxicity

Category 3

Harmful to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Solvent part expected to be biodegradable, but not the polymer or metal filler. The volatile solvent constituents will oxidize rapidly in air by photochemical reaction.

Section continued on the next page

841AR-P**PEN****Other Effects**

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities.

Actual VOC = 14% [236 g/L]; Regulated VOC = 502 g/L

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information**Ground**

Refer to TDG (Canadian Transportation of Dangerous Goods regulations) and USA DOT 49 CFR (Parts 100 to 185) Regulations.

Sizes 30 mL and under
Cat No. 841AR-P, 841AR-PCA

Excepted Quantity
Code **E2**



** Shipper Name

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 30 mL and under
Cat No. 841AR-P, 841AR-PCA

Excepted Quantity
Code **E2**



On air waybill, write:
"Dangerous Goods in
Excepted Quantities".

FOR REFERENCE ONLY

UN number: UN1263

Shipping Name: PAINT

Class: 3

Packing Group: II

Marine Pollutant: No

** Shipper Name

Section continued on the next page

841AR-P
PEN
Sea
Refer to IMDG regulations.

 Sizes 30 mL and under
 Cat No. 841AR-P, 841AR-PCA
Excepted Quantity
 Code **E2**

 In transport document,
 write:
 "Dangerous Goods in
 Excepted Quantities".

FOR REFERENCE ONLY

UN number: UN1263
Shipping Name: PAINT
Class: 3
Packing Group: II
Marine Pollutant: No

** Shipper Name

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information
Canada
Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)


All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA
Other Classifications
HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES


Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Section continued on the next page

841AR-P**PEN****CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain products that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains nickel (CAS# 7440-02-0, reportable quantity = 100 lb), n-butyl acetate (CAS# 123-86-4; reportable quantity = 5 000 lb [2 268 kg]) which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains acetone (CAS# 67-64-1), which is subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity)

This product contains nickel, which is listed as a carcinogen.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information**SDS Prepared by** Regulatory Department**Date of Review** 26 February 2020**Supersedes** 26 February 2020**Reason for Changes:** Added new part number.**Reference**

1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page

841AR-P**PEN**

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.