

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN	APVD	
H	-	A	INITIAL DRAWING	30 APR 2013	JS	GV
		B	REV PER ECO-16-014059	10JAN2017	WY	SZ
		BI	REMOVE PRELIMINARY STAMP	25MAY2019	OL	SZ

17,60

24,10

15,80

2

1

SCALE 2:1

NOTES:

1 USE FOR (SILVER PLATED) STANDARD POWER TIMER CONTACTS .
FOR CONTACTS PARTNUMBERS SEE DWG. C-1355048 VERSION A
ALLOWED MAX WIRE SIZE 10AWG.

2173200-1 AS SHOWN

2	LATCH	STAINLESS STEEL	NOT APPLICABLE
1	HOUSING	PBT 20%GF UL94V-0	NOT APPLICABLE
ITEM NO.	DESCRIPTION	MATERIAL	FINISH
THIS DRAWING IS A CONTROLLED DOCUMENT.			
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
		0 PLC ± 0,1 1 PLC ± 0,1 2 PLC ± 0,1 3 PLC ± - 4 PLC ± - ANGLES ± 2	
MATERIAL -		FINISH -	
DWN 24 oct 2012 J. Smits		 ELCON Mini, 4-position cable connector metal latch, 10AWG max. wire	
CHK 24 oct 2012 B. Mooij			
APVD 24 oct 2012 G. Verduijn			
PRODUCT SPEC -		NAME	
APPLICATION SPEC -		SIZE CAGE CODE DRAWING NO RESTRICTED TO	
WEIGHT -		A3 00779C- 2173200 -	
CUSTOMER DRAWING		SCALE 4:1 SHEET 1 OF 1 REV BI	

1470-19 (3/11)