



| | | | | | | | | | | | | |
|---|-----------------------------------|--|-------------------|-------------------|-------------------|-----------------|-----------------|------|------|------|------|--|
| Number of contacts | Standard | 3 | 4 | 5 | 5S | 6 | 7 | 7 | 8 | 12 | 14 | |
| Contact arrangement | DIN EN 61076-2-106 | 03-a | 04-a | 05-a | 05-b | 06-a | 07-a | 07-b | 08-a | 12-a | 14-a | |
| Contact arrangement | IEC 60130-9 ²⁾ | | | - | | | | | | | | |
| Rated voltage ³⁾ | IEC 60664-1 | 300 V (100 V) | 300 V (63 V) | 100 V (32 V) | 300 V (63 V) | 100 V (32 V) | 150 V (32 V) | | | | | |
| Rated voltage | UL 1977 | 250 V | | | | | | 60 V | | | | |
| Rated impulse withstand voltage ³⁾ | IEC 60664-1 | 1500 V (840 V) | 1200 V (500 V) | 1500 V (840 V) | 1200 V (500 V) | | | | | | | |
| Pollution degree ³⁾ | IEC 60664-1 | 1 (2) | | | | | | | | | | |
| Installation category | IEC 60664-1 | I | | | | | | | | | | |
| Insulation group | IEC 60664-1 | II, 400 ≤ CTI < 600 | | | | | | | | | | |
| Current rating | IEC 60512-5-2 UL 1977 | 10A/+40°C/+104°F | 7A/+40°C/+104°F | | | | 3A/+40°C/+104°F | | | | | |
| Insulation resistance | IEC 60512-3-1 | >10 ¹⁰ Ω ⁴⁾ | | | | | | | | | | |
| Contact resistance | IEC 60512-2-1 | <5m Ω | | | | | | | | | | |
| Climatic category | IEC 60668-1 | 40 / 100 / 56 | | | | | | | | | | |
| Temperatur range | IEC 60668-1 | -40°C...+100°C / -40°F...+212°F | | | | | | | | | | |
| IP degree | IEC 60529 | IP 40 | | | | | | | | | | |
| Insertion and withdrawal force | IEC 60512-13-2 | 25N | 30N | 35N | 50N | 55N | 60N | 50N | | | | |
| Mechanical operation | IEC 60512-9-1 | silver: ≥500 mating cycles / gold: ≥1000 mating cycles | | | | | | | | | | |
| Housing material | | brass and / or zinc die cast, nickel plated | | | | | | | | | | |
| Dielectric material | | thermoplastic | | | | | | | | | | |
| Contacts | | silver plated / gold plated | | | | | | | | | | |
| Termination technique | | solder | | | | | | | | | | |
| Flamability | | UL 94 V0 | | | | | | | | | | |
| locking system | IEC 60130-9 DIN EN 61076-2-106 | metal screw coupling; tightening torque 1 Nm | | | | | | | | | | |

²⁾ Edition 2000-05
³⁾ values in brackets are according to DIN EN 61076-2-106
⁴⁾ under operating conditions >10⁸ Ohm
 All technical data have been measured in a laboratory environment and can be different during practical usage of the product. Any product information is for descriptive usage only and not legally binding; particularly the information does not constitute or provide any legal guaranties. Do not connect or disconnect under load. Metal housing parts shall be securely incorporated to protected ground.
 Parts according to directive 2002/95/EG (RoHS).
 Remark for gold plated contacts:
 In order to avoid brittle inter-metallic connections, gold plated terminals have to be tin-plated in the solder area.

| | | | | | |
|---|--|-----------------|--------------|-----------------|-----------------|
| 14 (14-a) | Ag | T 3652 400 U | T 3652 420 U | T 3652 430 U | |
| | Au | T 3652 404 U | T 3652 424 U | T 3652 434 U | |
| 12 (12-a) | Ag | T 3637 400 U | T 3637 420 U | T 3637 430 U | |
| | Au | T 3637 404 U | T 3637 424 U | T 3637 434 U | |
| 8 (08-a) | Ag | T 3506 400 U | T 3506 420 U | T 3506 430 U | |
| | Au | T 3506 404 U | T 3506 424 U | T 3506 434 U | |
| 7 (07-b) | Ag | T 3486 400 U | T 3486 420 U | T 3486 430 U | |
| | Au | T 3486 404 U | T 3486 424 U | T 3486 434 U | |
| 7 (07-a) | Ag | T 3477 400 U | T 3477 420 U | T 3477 430 U | |
| | Au | T 3477 404 U | T 3477 424 U | T 3477 434 U | |
| 6 (6-a) | Ag | T 3402 400 U | T 3402 420 U | T 3402 430 U | |
| | Au | T 3402 404 U | T 3402 424 U | T 3402 434 U | |
| 5 (05-b) | Ag | T 3358 400 U | T 3358 420 U | T 3358 430 U | |
| | Au | T 3358 404 U | T 3358 424 U | T 3358 434 U | |
| 5 (05-a) | Ag | T 3362 400 U | T 3362 420 U | T 3362 430 U | |
| | Au | T 3362 404 U | T 3362 424 U | T 3362 434 U | |
| 4 (04-a) | Ag | T 3302 400 U | T 3302 420 U | T 3302 430 U | |
| | Au | T 3302 404 U | T 3302 424 U | T 3302 434 U | |
| 3 (03-a) | Ag | T 3262 400 U | T 3262 420 U | T 3262 430 U | |
| | Au | T 3262 404 U | T 3262 424 U | T 3262 434 U | |
| Contact arrangement View on mating side | Number of contacts (Contact arrangement acc. DIN EN 61076-2-106) | A=10,5mm [.413] | | A=14,5mm [.413] | A=19,5mm [.413] |

| | | | |
|--|-----------------------|-----------------------------|-------|
| Gewicht (errechnet) / Calc WT: 15,601 g | Zul. Abw./Tolerances: | Maßstab / Scale: 2:1 | A3 |
| Prüfmaß / Testdimension | | CUSTOMER DRAWING | |
| Teilindex Partindexnumber | DIN / ISO 13715 | male receptacle | |
| Datum/Date | Name | Status: Released | |
| Gez. Drawn | 30.03.2016 | Inspector: 31.05.2016 MGRIM | |
| Amphenol-Tuchel Electronics GmbH | | M CA-T 3XXX 4XX U | |
| 02 | 201600098 | 30.03.2016 | RSCHÄ |
| Index | Änderung/Description | Datum/Date | Name |
| | | 4.033.592 | |
| Ers. f. / Replacement for: M-CA-T 3XXX 4XX U Rev01 | | Blatt/Sheet 1 | |

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Ertragung vorbehalten.