

DETAILS


Product Number	C13015_FLARE-MINI-AD
Family	Flare
Type	Lens
Color	clear
Diameter	16 mm
Height	8,6 mm
Style	round
Optic Material	PMMA
Holder Material	
Fastening	glue
Status	production ready
ROHS Compliant	Yes
Date Updated	25/09/2015




OPTICAL PROPERTIES

LED	Viewing	Light	Effi-		
	Angle	Beam	ciency	cd/lm	Connector
XB-D	100+16 deg	Oval	93 %	1.200	-
XP-G	100+20 deg	Oval	94 %	1.100	-
XT-E	104+19 deg	Oval	94 %	1.100	-
XP-G2	97+24 deg	Oval	94 %	1.000	-
XP-E2	93+19 deg	Oval	94 %	1.300	-
XP-L	111+30 deg	Oval	90 %	0.710	-
XP-L2	100+30 deg	Oval	94 %	0.760	-
LUXEON C	sim: 15+94	Oval	sim: 93 %	sim: 1.350	-
NVSxx19A	100+20 deg	Oval	94 %	1.100	-
Oslon Square EC	92+21 deg	Oval	94 %	1.100	-
LH351Z	99+25 deg	Oval	94 %	1.100	-
Z8Y22P	112+24 deg	Oval	93 %	0.870	-


Relative intensity of CA13057&CA13058_FLARE-MINI-AD-XBD




Relative intensity of CA13057&CA13058_FLARE-MINI-AD-XPG




Relative intensity of CA13057&CA13058_FLARE-MINI-AD-XTE



Relative intensity of CA13057&CA13058_FLARE-MINI-AD-NVS19



Relative intensity of CA13057&CA13058_FLARE-MINI-AD-SQEC



D


C

B


A

4


4



Bottom view



Right view




Front view

3

3

2

2



Top view

This drawing is our property.
It can't be reproduced
or communicated without
our written agreement.



Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

DRAWING TITLE

Datasheet FLARE-MINI

DRAWN BY

as

DATE

1.8.2012

CHECKED BY

sn

DATE

1.8.2012

DESIGNED BY

pl

DATE

27.2.2012

SIZE

A4

PART NUMBER

SCALE

2:1

WEIGHT

REV

001

SHEET

1/1


1

1


D

A


Luminaire: Ledil Oy C13015_FLARE-MINI-AD (CREE XP-G2 (99 lm @ 250 mA)) Efficiency=94%
Lamps: 1 x CREE XP-G2 (99 lm @ 250 mA)



Luminaire: Ledil Oy C13015_FLARE-MINI-AD (CREE XP-E2 (92 lm @ 250 mA)) Efficiency=94%
Lamps: 1 x CREE XP-E2 (92 lm @ 250 mA)




Luminaire: LEDiL Oy C13015_FLARE-MINI-AD_(XP-L)
Lamps: 1 x Cree_XP-L_127.813lm@250mA_P=0.73723W_I=249.9mA




Luminaire: Ledil C13015_FLARE-MINI-AD_(XP-L2)

Lamps: 1 x Cree_XP-L2_(XPLWT-00-0000-000HU630G)_115.505lm@250mA_P=0.72165W_I=0.25A




Luminaire: LEDil Oy C13015_FLARE-MINI-AD_(LH351Z)

Lamps: 1 x Samsung LH351Z (90.14lm @ 250mA) CCT=6500K P=0.7W I=250mA




Luminaire: Ledil C13015_FLARE-MINI-AD_(Z8Y22P)

Lamps: 1 x Seoul_Z8Y22P_(W6E2G)_129.545lm@250mA_P=0.711175W_I=0.25A



Luminaire: Ledil Oy C13015_FLARE-MINI-AD (CREE XP-G2 (99 lm @ 250 mA)) Efficiency=94%
Lamps: 1 x CREE XP-G2 (99 lm @ 250 mA)




cd/klm

— C0 - C180

— C90 - C270


Luminaire: Ledil Oy C13015_FLARE-MINI-AD (CREE XP-E2 (92 lm @ 250 mA)) Efficiency=94%
Lamps: 1 x CREE XP-E2 (92 lm @ 250 mA)



cd/klm


— C0 - C180 — C90 - C270

Luminaire: LEDiL Oy C13015_FLARE-MINI-AD_(XP-L)
Lamps: 1 x Cree_XP-L_127.813lm@250mA_P=0.73723W_I=249.9mA



Luminaire: Ledil C13015_FLARE-MINI-AD_(XP-L2)

Lamps: 1 x Cree_XP-L2_(XPLWT-00-0000-000HU630G)_115.505lm@250mA_P=0.72165W_I=0.25A



cd/klm


— C0 - C180

— C90 - C270

$\eta = 94\%$

Luminaire: LEDil Oy C13015_FLARE-MINI-AD_(LH351Z)

Lamps: 1 x Samsung LH351Z (90.14lm @ 250mA) CCT=6500K P=0.7W I=250mA



cd/klm


— C0 - C180

— C90 - C270

$\eta = 94\%$

Luminaire: Ledil C13015_FLARE-MINI-AD_(Z8Y22P)

Lamps: 1 x Seoul_Z8Y22P_(W6E2G)_129.545lm@250mA_P=0.711175W_I=0.25A



cd/klm

— C0 - C180

— C90 - C270

η = 93%

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.