

G2-LAURA-D-P

~13° diffused spot beam. Assembly with thinner white holder, installation tape and location pins.

SPECIFICATION:

Dimensions	21.6 x 21.6 mm
Height	13.1 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish
LAURA-D	Single lens	PMMA	clear	
LAURA-LT-PIN-XP-HLD-WHT	Holder	PC	white	
ROSE-TAPE	Tape	Acrylic foam	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA13629_G2-LAURA-D-P	Single lens	1440	360	180	5.9
» Box size: 451 x 254 x 152 mm					







See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):

CREE LED

LED XB-H
 FWHM / FWTM 19.0° / 41.0°
 Efficiency 83 %
 Peak intensity 4.8 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:




CREE LED

LED XP-E
 FWHM / FWTM 13.0° / 31.0°
 Efficiency 93 %
 Peak intensity 9.3 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:





CREE LED

LED XP-E2
 FWHM / FWTM 16.0° / 37.0°
 Efficiency 83 %
 Peak intensity 6.1 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:



CREE LED



LED XP-G2
 FWHM / FWTM 19.0° / 40.0°
 Efficiency 83 %
 Peak intensity 5.1 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):


CREE LED

LED XP-L HD
 FWHM / FWTM 21.0° / 45.0°
 Efficiency 81 %
 Peak intensity 3.6 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:





CREE LED

LED XP-L2
 FWHM / FWTM 22.0° / 48.0°
 Efficiency 84 %
 Peak intensity 3.5 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:





CREE LED

LED XT-E
 FWHM / FWTM 19.0° / 41.0°
 Efficiency 82 %
 Peak intensity 4.7 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:











LUMILEDS









LED LUXEON 3030 2D (Round LES)
 FWHM / FWTM 18.0° / 38.0°
 Efficiency 87 %
 Peak intensity 5.4 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:









OPTICAL RESULTS (MEASURED):

<p>LUMILEDS</p> <p>LED LUXEON TX FWHM / FWTM 18.0° / 40.0° Efficiency 86 % Peak intensity 5.2 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>NICHIA</p> <p>LED NCSxx19A FWHM / FWTM 19.0° / 41.0° Efficiency 87 % Peak intensity 5 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>NICHIA</p> <p>LED NCSxx19B FWHM / FWTM 17.0° / 38.0° Efficiency 83 % Peak intensity 5.4 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>NICHIA</p> <p>LED NVSW219D FWHM / FWTM 18.0° / 40.0° Efficiency 94 % Peak intensity 5 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		

OPTICAL RESULTS (MEASURED):

<p>NICHIA</p> <p>LED NVSxx19A FWHM / FWTM 20.0° / 43.0° Efficiency 81 % Peak intensity 4.2 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>NICHIA</p> <p>LED NVSxx19B/NVSxx19C FWHM / FWTM 19.0° / 42.0° Efficiency 83 % Peak intensity 4.9 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSLOM Square EC FWHM / FWTM 19.0° / 40.0° Efficiency 82 % Peak intensity 4.9 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>SAMSUNG</p> <p>LED LH351D FWHM / FWTM 21.0° / 46.0° Efficiency 93 % Peak intensity 3.8 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		


OPTICAL RESULTS (MEASURED):

<p> SEOUL SEMICONDUCTOR</p> <p>LED Z5M1/Z5M2</p> <p>FWHM / FWTM 18.0° / 39.0°</p> <p>Efficiency 83 %</p> <p>Peak intensity 4.9 cd/m</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p> SEOUL SEMICONDUCTOR</p> <p>LED Z5M3</p> <p>FWHM / FWTM 19.0° / 42.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 4.5 cd/m</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		

OPTICAL RESULTS (SIMULATED):


CREE LED

LED XHP35 HI
 FWHM / FWTM 14.0° / 26.0°
 Efficiency 94 %
 Peak intensity 12.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




CREE LED

LED XP-G3
 FWHM / FWTM 14.0° / 28.0°
 Efficiency 93 %
 Peak intensity 11.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




CREE LED

LED XQ-E HD
 FWHM / FWTM 10.8° / 21.2°
 Efficiency 94 %
 Peak intensity 20.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:








NICHIA

LED NS9x383
 FWHM / FWTM 16.0° / 30.0°
 Efficiency 94 %
 Peak intensity 8.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (SIMULATED):

<p>OSRAM Opto Semiconductors</p> <p>LED: KW CULPM1.TG</p> <p>FWHM / FWTM: 10.0° / 20.0°</p> <p>Efficiency: 96 %</p> <p>Peak intensity: 21.8 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED: OSLO Signal</p> <p>FWHM / FWTM: 10.0° / 20.0°</p> <p>Efficiency: 95 %</p> <p>Peak intensity: 24.2 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: Red</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED: OSLO Square CSSRM2/CSSRM3</p> <p>FWHM / FWTM: 12.0° / 25.0°</p> <p>Efficiency: 96 %</p> <p>Peak intensity: 14.5 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED: OSLO Square Flat</p> <p>FWHM / FWTM: 9.0° / 19.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 26.1 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	 

OPTICAL RESULTS (SIMULATED):

<p>OSRAM Opto Semiconductors</p> <p>LED: OSLOM SSL 80</p> <p>FWHM / FWTM: 10.0° / 22.0°</p> <p>Efficiency: 95 %</p> <p>Peak intensity: 18.7 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p>SEOUL SEMICONDUCTOR</p> <p>LED: Z8Y22P</p> <p>FWHM / FWTM: 13.0° / 25.0°</p> <p>Efficiency: 97 %</p> <p>Peak intensity: 13.6 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)