





| APPLICABLE STANDARD   |   |                          |   |                                     |   |
|---|---|--------------------------|---|-------------------------------------|---|
| RATING  | OPERATING TEMPERATURE RANGE   | -55°C TO +85°C           | STORAGE TEMPERATURE RANGE   | -10°C TO +50°C(PACKED CONDITION)    |   |
|   | VOLTAGE   | 30V AC/DC                | OPERATING OR STORAGE HUMIDITY RANGE   | RELATIVE HUMIDITY 90%MAX(NOT DEWED) |   |
|   | CURRENT   | 0.2A                     | APPLICABLE CABLE  | t=0.2±0.03mm, GOLD PLATING          |   |
| SPECIFICATIONS  |   |                          |   |                                     |   |
| ITEM  | TEST METHOD   |                          | REQUIREMENTS  | QT                                  | AT  |
| CONSTRUCTION  |   |                          |   |                                     |   |
| GENERAL EXAMINATION   | VISUALLY AND BY MEASURING INSTRUMENT.   |                          | ACCORDING TO DRAWING.   | ×                                   | ×   |
| MARKING   | CONFIRMED VISUALLY.   |                          |   | ×                                   | ×   |
| ELECTRIC CHARACTERISTICS  |   |                          |   |                                     |   |
| VOLTAGE PROOF   | 90V AC FOR 1 min.   |                          | NO FLASHOVER OR BREAKDOWN.  | ×                                   | ×   |
| INSULATION RESISTANCE   | 100V DC.  |                          | 50MΩ MIN.   | ×                                   | ×   |
| CONTACT RESISTANCE  | AC 20mV MAX (1KHz), 1mA.  |                          | 100mΩ MAX.<br>INCLUDING FPC BULK RESISTANCE (L=12mm)  | ×                                   | ×   |
| MECHANICAL CHARACTERISTICS  |   |                          |   |                                     |   |
| VIBRATION   | FREQUENCY 10 TO 55 Hz, HALF AMPLITUDE<br>0.75 mm FOR 10 CYCLES IN 3 AXIAL DIRECTIONS.         |                          | ① NO ELECTRICAL DISCONTINUITY OF 1 μ s.<br>② CONTACT RESISTANCE: 100mΩ MAX.<br>③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.                             | ×                                   | —   |
| SHOCK   | 981 m/s <sup>2</sup> , DURATION OF PULSE 6ms AT 3 TIMES<br>IN 3 BOTH AXIAL DIRECTIONS.        |                          |   | ×                                   | —   |
| MECHANICAL OPERATION  | 10 TIMES INSERTIONS AND EXTRACTIONS.  |                          | ① CONTACT RESISTANCE: 100mΩ MAX.<br>② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.  | ×                                   | —   |
| FPC RETENTION FORCE   | MEASURED BY APPLICABLE FPC.<br>(THICKNESS OF FPC SHALL BE t=0.20mm<br>AT INITIAL CONDITION.)  |                          | DIRECTION OF INSERTION: 0.15 N × n MIN.<br>(note 1)   | ×                                   | —   |
| ENVIRONMENTAL CHARACTERISTICS   |   |                          |   |                                     |   |
| CORROSION SALT MIST   | EXPOSED AT 35±2°C, 5% SALT WATER SPRAY<br>FOR 96h.  |                          | ① CONTACT RESISTANCE: 100mΩ MAX.<br>② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.<br>③ NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR. | ×                                   | —   |
| RAPID CHANGE OF TEMPERATURE   | TEMPERATURE -55→+15 TO +35→+85→+15TO+35 °C<br>TIME 30 → 2~3 → 30 → 2~3 min<br>UNDER 5 CYCLES. |                          |   | ×                                   | —   |
| DAMP HEAT (STEADY STATE)  | EXPOSED AT 40±2°C,<br>RELATIVE HUMIDITY 90 TO 95%, 96h.                                       |                          | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.  | ×                                   | —   |
|   |   |                          |   |                                     |   |
|   | COUNT   | DESCRIPTION OF REVISIONS | DESIGNED  | CHECKED                             | DATE  |
|  |   |                          |   |                                     |   |
| REMARK  |   |                          | APPROVED  | NM.NISHIMATSU                       | 11.09.14  |
|   |   |                          | CHECKED   | HS.SAKAMOTO                         | 11.09.12  |
|   |   |                          | DESIGNED  | TY.MOGI                             | 11.09.12  |
| Unless otherwise specified, refer to JIS C 5402.                                    |   |                          | DRAWN   | TY.MOGI                             | 11.09.12  |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test                      |   |                          | DRAWING NO.   |                                     | ELC4-323213-01  |
|  | SPECIFICATION SHEET   |                          | PART NO.  | FH26W-19S-0.3SHW(05)                |   |
|   | HIROSE ELECTRIC CO., LTD.   |                          | CODE NO.  | CL580-2437-9-05                     |  1/2 |

| SPECIFICATIONS  |  |  |             |                      |   |
|---|--|--|-------------|----------------------|---|
| ITEM  | TEST METHOD  | REQUIREMENTS   | QT          | AT                   |   |
| DAMP HEAT, CYCLIC   | EXPOSED AT -10 TO +65 °C<br>RELATIVE HUMIDITY 90 TO 96 %<br>10 CYCLES, TOTAL 240h.   | ① CONTACT RESISTANCE: 100mΩ MAX.<br>② INSULATION RESISTANCE: 1MΩ MIN.<br>(AT HIGH HUMIDITY)<br>③ INSULATION RESISTANCE: 50MΩ MIN.<br>(AT DRY)<br>④ NO DAMAGE, CRACK AND LOOSENESS<br>OF PARTS. | X           | —                    |   |
| DRY HEAT  | EXPOSED AT 85±2°C, 96h.  | ① CONTACT RESISTANCE: 100mΩ MAX.<br>② NO DAMAGE, CRACK AND LOOSENESS<br>OF PARTS.  | X           | —                    |   |
| COLD  | EXPOSED AT -55±3°C, 96h.   |  | X           | —                    |   |
| SULPHUR DIOXIDE<br>[JIS C 0090]   | EXPOSED AT 40±2°C,<br>RELATIVE HUMIDITY 80±5 %,<br>25±5 PPM FOR 96h.   | ① CONTACT RESISTANCE: 100mΩ MAX.<br>② NO DAMAGE, CRACK AND LOOSENESS<br>OF PARTS.<br>③ NO EVIDENCE OF CORROSION WHICH<br>AFFECTS TO OPERATION OF CONNECTOR.                                    | X           | —                    |   |
| HYDROGEN SULPHIDE<br>[JIS C 0092]   | EXPOSED AT 40±2°C,<br>RELATIVE HUMIDITY 80±5 %,<br>10 ~ 15 PPM FOR 96h.  |  | X           | —                    |   |
| SOLDERABILITY   | SOLDERED AT SOLDER TEMPERATURE, 235±5°C<br>FOR IMMERSION DURATION, 2±0.5 sec.  | A NEW UNIFORM COATING OF SOLDER<br>SHALL COVER A MINIMUM OF 95 %<br>OF THE SURFACE BEING IMMERSED.   | X           | —                    |   |
| RESISTANCE TO<br>SOLDERING HEAT   | 1) REFLOW SOLDERING:<br>PEAK TMP. 250°C MAX.<br>REFLOW TMP. 230°C MIN FOR 60 sec.<br>2) SOLDERING IRONS:<br>TMP. 350±10°C FOR 5±1 sec. | NO DEFORMATION OF CASE<br>OF EXCESSIVE LOOSENESS<br>OF THE TERMINALS.<br>(note 2)  | X           | —                    |   |
| <p>(note 1)</p> <p>THIS PRODUCT HAS FLIP-LOCK CONSTRUCTION. FASTEN FPC ON PCB OR SOMETHING FIXED<br/>IF FORCE IN VERTICAL DIRECTION SHALL BE PREDICTED.</p> <p>(note 2)</p> <p>BLISTERS WHICH MAY OCCUR IN HOUSING DO NOT AFFECT PRODUCT PERFORMANCE.</p> |  |  |             |                      |   |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test  |  |  | DRAWING NO. |                      | ELC4-323213-01  |
| <b>HRS</b>  | SPECIFICATION SHEET  |  | PART NO.    | FH26W-19S-0.3SHW(05) |   |
|   | HIROSE ELECTRIC CO., LTD.  |  | CODE NO     | CL580-2437-9-05      |  2/2 |