

Specification Sheet

Part Number: T50RSF0M4



Arrowhead Push-Mount Cable Tie, 8.3"L, 50lb, 0.04"–0.14" Panel Thickness, PA66HS, Black, 1000/pkg

Article Number	126-01004
Type	T50RSF(U)
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">•All-in-one bundling and fastening solution reduces costs and assembly time.•The arrowhead design of these ties offers a low insertion force and a high extraction force.•High-spec materials and superior design deliver versatility, performance and value.
Quantity Per	bag

Product Description

One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. The arrowhead design of this push mount inserts easily and locks securely in place. HellermannTyton's one-piece mounting ties combine high-specification materials with superior design to deliver dependable performance in a range of applications.

Short Description	Arrowhead Push-Mount Cable Tie, 8.3"L, 50lb, 0.04"–0.14" Panel Thickness, PA66HS, Black, 1000/pkg
Global Part Name	T50RSF(U)-PA66HS-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.3
Length L (Metric)	210.0
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.6
Bundle Diameter Max (Imperial)	1.7

Bundle Diameter Max (Metric)	44.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2
Height H (Imperial)	.30
Height H (Metric)	7.50
Panel Thickness Min(Imperial)	0.039
Panel Thickness Max(Imperial)	0.14
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	3.56
Mounting Hole Diameter D (Imperial)	0.25 - 0.28
Mounting Hole Diameter D (Metric)	6.4 - 7.1 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.1
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66HS

Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
ROHS Complaint	Yes
Certification/Specification WEB	UL-ZODZ2.E64139
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909987