



(without protection cap)

(without protection cap)

Loading-Plan

A — red — B
B — green — A

- Protection level: IP20
- Temperature range: -10° C ...+70° C

11	33012410500006	FO Multi Mode, 50/125 μm	50000 ± 500
10	33012410100006	FO Multi Mode, 50/125 μm	10000 ± 100
9	33012410090006	FO Multi Mode, 50/125 μm	9000 ± 90
8	33012410080006	FO Multi Mode, 50/125 μm	8000 ± 80
7	33012410070006	FO Multi Mode, 50/125 μm	7000 ± 70
6	33012410060006	FO Multi Mode, 50/125 μm	6000 ± 60
5	33012410050006	FO Multi Mode, 50/125 μm	5000 ± 50
4	33012410040006	FO Multi Mode, 50/125 μm	4000 ± 40
3	33012410030006	FO Multi Mode, 50/125 μm	3000 ± 30
2	33012410020006	FO Multi Mode, 50/125 μm	2000 ± 20
1	33012410010006	FO Multi Mode, 50/125 μm	1000 ± 15
Cont. no.	Part. no.	Type of cable	Dim. a[mm]

	All rights reserved Department EC PD - RO	All Dimensions in mm Original Size DIN A3		Scale 1.5:1	Free size tol.	Ref. Sub.	
		Created by DRAGHICI	Inspected by STOICA	Standardisation HOFFMANN	Date 2012-09-14	State Final Release	
Title Fiber optic jumper cord						Doc-Key / ECM-Nr. 100197832/UGD/006/B 50000055244	
HARTING Electronics GmbH D-32339 Espelkamp		Type TB	Number 3301241XXX0006			Rev. B	Page 1/1