

## Specification Sheet

Part Number: 151-10915



Q Tie Mount with Adhesive, 1.2" x 1.2" x 0.21", 4 way entry for Q18 thru Q50 ties, PA66, Black, 100/bag

|                                |  |
|--------------------------------|--|
| <b>Article Number</b>          | 151-10915  |
| <b>Type</b>                    | QM30A  |
| <b>Color</b>                   | Black (BK)   |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>• 2- or 4-way entry options for the Q Tie, offering flexibility and stability</li></ul>  |
| <b>Quantity Per</b>            | bag  |
| <b>Product Description</b>     | Q Mounts are designed to work exclusively with the Q Tie cable tie series. This mounting component is available with adhesive or can be secured with screws. The Q Mount allows either a 2- or 4-way entry for the Q Tie, providing a quick and simple insertion into the mount. Once in place, the Q Tie will not slip out, even in vertical mounting applications. |
| <b>Short Description</b>       | Q Tie Mount with Adhesive, 1.2" x 1.2" x 0.21", 4 way entry for Q18 thru Q50 ties, PA66, Black, 100/bag  |

Global Part Name

QM30A-PA66-BK

Length L (Imperial)

1.2

Length L (Metric)

30.0

Fixation Method

Screw Mounting and Adhesive

Width W (Imperial)

1.2

Width W (Metric)

30.0

Height H (Imperial)

0.21

Height H (Metric)

4.5

Cable Tie Width Max (Imperial)

0.2

Cable Tie Width Max (Metric)

5.1

Mounting Hole Diameter D (Imperial)

0.16

Mounting Hole Diameter D (Metric)

4.1 mm

Mounting Hole Diameter D Min (Imperial)

0.16

Mounting Hole Diameter D Max (Metric)

4.1

Mounting Hole Centers (Imperial)

0.83

|                                       |   |
|---------------------------------------|---|
| <b>Material</b>                       | Polyamide 6.6 (PA66)                            |
| <b>Material Shortcut</b>              | PA66  |
| <b>Adhesive</b>                       | Synthetic rubber with base of polyethylene foam |
| <b>Flammability</b>                   | UL 94 V2 (excluding adhesive)                   |
| <b>Halogen free</b>                   | Yes   |
| <b>Adhesive Operating Temperature</b> | -40°F to +140°F (-40°C to +60°C)                |
| <b>Operating Temperature (Metric)</b> | -40°F to +185°F (-40°C to +85°C)                |
| <b>Reach Complaint(Article 33)</b>    | Yes   |
| <b>ROHS Complaint</b>                 | Yes   |
| <b>Package Quantity(Imperial)</b>     | 100   |
| <b>Package Quantity (Metric)</b>      | 100   |
| <b>Customs Number</b>                 | 3926909988                                      |
| <b>Content Unit(BMEcat)</b>           | pcs.  |