

Datasheet for part number CA06COME28A16P

Our Catalog Part Number: CA06COM-E28A16P

Brand: Cannon Product Category: Circular Product Line: CA Bayonet Series: CA COM

Product Datasheet		
Thread	Connector with Threaded Coupling	
Shell Style	Plug, straight	
Endbell Style	Endbell with clamp and bushing (w/o grommet and ferrule)	
Gender	Pin	
Shell Size	28	
Contact Arrangement	28A16	
Number of contacts	4 contacts size 4, 5 contacts size 16	
Contact Type	Solder Cup	
Contact Plating	Hard silver	
Contacts installed	yes	
Contact Rating at +20 °C (68 °F) (Size 15/15S/16/16S)	22 A	
Contact Rating at +20 °C (68 °F) (Size 160/4)	135 A	
Contact Resistance (Size 15/15S/16/16S)	6 mΩ	
Contact Resistance (Size 160/4)	0,5 mΩ	
Operating Voltage	In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41.	
Insulator Resistance	≥1000 MΩ	
Test Voltage	1600 Vrms	
Air and Creepage Paths (Min)	1,1 mm	
Ambient Temperature	Standard insulator material -55°/+125°C (-67/257°F)	
Safety Provisions	IP67 (only applies if a grommet is used)	
Mating Cycles	500 min	
Sep. Force per Contact (Size 15/15S/16/16S)	1,0 N	
Sep. Force per Contact (Size 160/4)	4,0 N	
Gauge	For infos on Gauge please see catalog VG95234, part 1	
Coupling Torque	Closing: 7 Nm max / Opening: 0,92 Nm min	
Contact Retention (Size 15/15S/16/16S)	35 N	
Contact Retention (Size 160/4)	90 N	
Shell Material	Aluminium alloy	
Shell Plating	Nickel plated	
Insulator and Gromet Material	CR-Elastomere	
Contact Material	Copper alloy	
Harnessing Info: Contact Cross-Section	See assembly instruction	
Harnessing Info: Insulator Diameter	See assembly instruction	
Wire Stripping (Size 15/15S/16/16S)	6,2 mm	
Wire Stripping (Size 160/4)	11,8 mm	



Datasheet for part number CA06COME28A16P

Our Catalog Part Number: CA06COM-E28A16P				
Brand: Cannon	Product Category: Circular	Product Line: CA Bayonet	Series: CA COM	

Product Datasheet	
General Info	All tests in accordance with VG95319 and/or if applicable with VG95210 except salt spray resistance and heat and humidity endurance test