

1

2

3

4



HARTING PushPull V4, Receptacle RJ45, Cat. 6A, 8-pole

RoHS
compliant ✓

General information


Design	PushPull V4 receptacle compatible to IEC/PAS 61076-3-106 variant 04
No. of contacts	8
Temperature range	-40°C ... +85°C
Mating cycles	750
IP-Protection	IP 65/67/68 (1m, 48h) when mated
Insertion force	50 N
Withdrawal force	50 N
Category of transmission	Cat. 6A acc to IEC 60603-7-51
RoHS - compliant	Yes
UL file	pending

Insulator material

Material	PC (Polycarbonate)
Color	yellow
UL classification	UL 94 V0
Material group acc. IEC 60664-1	PC: III (200)

Contact material

Contact material	Copper alloy
Plating contact zone	Au over Ni



All Dimensions in mm
Original Size DIN A4

Scale
1:1

Free size tol.

Ref.

Sub. DS 09456101000 / ECM 500000117443 / 2017-07-05



All rights reserved

Department EC PD - DE

Created by
HASELOH

Inspected by
LUECKEMEIERM

Standardisation
HOFFMANN

Date
2017-07-21

State
Final Release

Title
HARTING PushPull V4, Receptacle, RJ 45, Cat. 6A, 8-pole

Doc-Key / ECM-Nr.
100680047/UGD/000/B
500000121889

HARTING Electronics GmbH
D-32339 Espelkamp

Type
DS

Number
09456101000

Rev.
B

Page
1/1