

Housing cover - BC 17,8 DKL S TRANS - 2896102

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Installation component housing, Transparent hinged cover, Including insertion plate, width: 17.8 mm, color: transparent/light gray (7035)



Your advantages

- Conforms to DIN EN 43880
- ▼ Tool-free mounting
- Available in overall widths from one to nine width units (17.8 mm ... 161.6 mm)
- ✓ Inflammability class V0 according to UL 94
- ✓ Variety of connection technologies
- Can be mounted on the DIN rail or the wall
- Optional with bus connector for DIN rail mounting



Key Commercial Data

Packing unit	10 pc
GTIN	4 046356 096638
GTIN	4046356096638

Technical data

Item properties

Brief article description	Housing cover
Туре	BC 17,8 DKL S TRANS
Order No.	2896102
Housing type	Installation component housing
Housing series	BC
Туре	Transparent hinged cover
Mounting type	hinged and can be sealed

Dimensions



Housing cover - BC 17,8 DKL S TRANS - 2896102

Technical data

ъ.	
I)ıme	nsions
D0	11010110

Width [w]	17.8 mm
Height [h]	45 mm

Material data

Color (RAL)	transparent/light gray (7035)
Flammability rating according to UL 94	V0

Ambient conditions

Ambient temperature (storage/transport)	-40 °C 70 °C
Ambient temperature (assembly)	-5 °C 100 °C
Ambient temperature (operation)	-40 °C (depending on power dissipation)

Packaging information

Pieces per package	10
Denomination packing units	Pcs.

Standards and regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

UL Recognized / EAC

Ex Approvals

Approval details

UL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 240868

EAC **EHI** B.01742



Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com