



**Technical specification:**

Rated voltage: IEC 61076-2-101	4pos 250 V
Current rating: IEC 61076-2-101	4 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	>=100

**Materials:**

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Coupling screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

**Installation specification:**

Recommended torque:	0,6 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 13: 36-000220

**Contact assignment:**

- 1 brown
- 2 white
- 3 blue
- 4 black

Part no:	Description:	Length L:	Cable:
43-14440	SAL - 12 - RSW4 - 2 / K1 / A1090	2m	TPU, UL 20549, black, 4x0,34mm <sup>2</sup> Cable: 781-K13400
43-14441	SAL - 12 - RSW4 - 3 / K1 / A1090	3m	
43-14442	SAL - 12 - RSW4 - 5 / K1 / A1090	5m	
43-14443	SAL - 12 - RSW4 - 10 / K1 / A1090	10m	
43-xxxxx	SAL - 12 - RSW4 - ... / K1 / A1090	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	dim. in mm		title: <b>Male connector M12x1 angled</b>		
		date			name
	tolerance of cable:	$L \leq 4m: L + 40mm$ $L > 4m: L + 1\%$	drawn	15.11.10	Franz
	general tolerance:	$0 \pm 0,50mm$ $0,0 \pm 0,25mm$ $0,00 \pm 0,10mm$	appd.	15.11.10	Mankopf
	THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH				dwg no: <b>43K1A1234</b>
				part no: see table	