	т <u>О</u> т	m		0	₩	A]
CHARCTERSTICS Solidard: Board on ML DT: 38999 Series II Solidard: Board on ML DT: 38999 Series II Solidard: Board on ML DT: 38999 Series II Solidard: Solid on Cooper Alloy Solid on Cooper Alloy Solid minimum Oversality minimum	4						4
CHARACTERISTICS Standard: Based on ML-DT-38999 Series III Shelf Material : Aluminium Shelf Material : Aluminium Shelf Material : Compactor dimension Units : Editor dimension Shelf Material : Shelf Material Shelf Material : Compactor dimension Units : Compactor dimension : Compactor dimension				LAYOUT SHOWN AS E	XAMPLE		3
CHARACTERISTICS Standard: Based on ML-DT-38999 Series III Shelf Material : Aluminium Shelf Material : Aluminium Shelf Material : Compactor dimension Units : Editor dimension Shelf Material : Shelf Material Shelf Material : Compactor dimension Units : Compactor dimension : Compactor dimension	Keying Shown	as example					
-Sheddri: Based on ML-DTL-3999 Series III Shell Material: :: Aluminium Shell Material: :: Aluminium -Shell Material: :: Aluminium -Insolator: :: Thermoplastic -Contact Plating: :: :: Stopper Alby -Seal: Screene: :: :: :: :: :: :: :: :: :: :: :: :: :							
	-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
-Contact Plating : Gold over cooper Alloy 0.8µm minimum PR Not Listed 2 -Durability : S00 Mating cycles -Delivered with Souriau contacts and Accessories PN: 8D521W35BB 2 -Temperature Range : 63:55 g ± 10% A 10-10-2016 First Release Mot Listed A -Mass : 63:55 g ± 10% Mot DN* Mod DN* Mod DN* BASIC SERIES: 8D 5 21 W 35 B ORIENTATION: B SOURIAU WWW.SOURIAU.COM This document is the property of SHELL SZE: 21 CONTACT TYPE: Standard Crimp Contact SOURIAU WWW.SOURIAU.COM This document is the property of PLATING: W = 0live drab Cadmium CONTACT TYPE: SOCKET(S00 Matings) TOIMAT SOURIAU SOURIAU DRG N° SHEET V0IMAT SOURIAU DRG N° SHEET 1/2	-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	Z 31 Max	due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
- Delivered with Souriau contacts and Accessories - Temperature Range : 65°C to +175°C. - Salt Spray : 500 hours - Mass : 63.55 g ± 10% BASIC SERIES: 8D 5			[2
-Temperature Range :-65°C to +175°C -Salt Spray : 500 hours -Mass ::63.55 g ± 10% BASIC SERIES: BD SHELL TYPE :Plug with RFI Shielding CONTACT TYPE :Standard Crimp Contact SHELL SIZE : 21 Image: Contact Type: :Standard Crimp Contact PLATING : W = Olive drab Cadmium			PN: 8D521W35BB				
-Salt Spray : 500 hours -Mass : 63.55 g ± 10% Mass : 63.55 g ± 10% BASIC SERIES: 8D 5 21 W 35 B B CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21 PLATING : W = Olive drab Cadmium CONTACT TYPE : Slandard Crimp Contact SHELL SIZE : 21 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 M							
-Mass : 63.55 g ± 10% -Mass : 63.55 g ± 10% BASIC SERIES: 8D 5 - 21 W 35 B B SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21 PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) CO			A 10-10-2016	First Release			
BASIC SERIES: 8D 5 21 W 35 B B Image: Contact Type : Standard Crimp Contact SCALE Aluminium Plug 8D series 859 SHELL SIZE : 21 CONTACT TYPE : Standard Crimp Contact ORIENTATION : B SOURIAU This document is the property of SOURIAU.COM SOURIAU This document is the property of SOURIAU SOURIAU SOURIAU This document is the property of SOURIAU SOURIAU SOURIAU SOURIAU This document is the property of SOURIAU <td></td> <td></td> <td>ISS DATE</td> <td>Latest modification - by</td> <td></td> <td>MOD N°</td> <td>_</td>			ISS DATE	Latest modification - by		MOD N°	_
BASIC SERIES: 8D 5 - 21 W 35 B B SHELL TYPE : Plug with RFI Shielding General linear NPRDS / PROJECT CONTACT TYPE : Standard Crimp Contact ORIENTATION : B NA SOURIAU Souriau SHELL SIZE : 21 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) SOURIAU This document is the property of communicated without permission PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 21-35 FORMAT SOURIAU DRG N° communicated without permission SHEET A3 8D521W35BB-C 1/2					CUSTOMER DRAV		_
BASIC SERVES. ab 3 2 1 W 33 b b Image: Server			TITLE	TILE Aluminium Plug 8D series			
CONTACT TYPE : Standard Crimp Contact ORIENTATION : B SOURIAU This document is the property of SOURIAU.COM SHELL SIZE : 21 CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 21-35 FORMAT SOURIAU DRG N° communicated without permission PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 21-35 FORMAT SOURIAU DRG N° sheet SHEET 1/2 Image: Additional descent de				Tolerances:		ECT	-
SHELL SIZE : 21 CONTACT TYPE : SOCKET(500 Matings) SOURIAU it must not be reproduced or communicated without permission PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 21-35 FORMAT SOURIAU DRG N° SHEET A3 8D521W35BB-C 1/2					CO11		- '
PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 21-35 FORMAT SOURIAU DRG N° SHEET A3 8D521W35BB-C 1/2			SOURIAU	WWW.SOURIAU.C	JOIVI it must not be	reproduced or	
A3 8D521W35BB-C 1/2			FORMAT	CUIDIALI			-
		CONTACT LATOUT : 21-35					

r	工	۵	г	m	D	0	
4		Contact Layout					
	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Y-axis (mm) Contact position ID X-axis (mm) Y-axis (mm) +426 (10.82) 41 098 (2.49) 322 (8.18) +426 (10.82) 41 098 (2.49) 322 (8.18) >-020 (7.67) 43 288 (6.55) 220 (5.57) >-020 (7.67) 44 314 (7.00) 141 (1.28) +227 (5.77) 45 332 (8.43) 048 (1.22) +141 (3.58) 46 332 (8.43) 048 (1.22) -048 (1.22) 47 311 (7.300) +.141 (3.58) -048 (1.22) 48 258 (6.55) +.220 (5.59) -141 (3.58) 49 184 (4.67) +.280 (7.11) -227 (5.77) 50 098 (4.24) +.280 (7.11)					
ω	13 +.146 (3.71) 14 +.053 (1.35) 15 053 (1.35) 16 146 (3.71)	-362 (9.19) 52 +.048 (1.22) +.241 (6.12) -404 (10.26) 53 +.134 (3.40) +.199 (5.05) -426 (10.82) 54 +.208 (5.28) +.139 (3.53) -426 (10.82) 55 +.237 (6.02) +.048 (1.22) -404 (10.26) 56 +.237 (6.02) 048 (1.22) -362 (9.19) 57 +.208 (5.28) 139 (3.53) Contacts (Insert arrangement 21-35)					
	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	T-40/3 (mm) position ID (mm) A-40/3 (mm) T-40/3 (mm) -302 (7 67) 58 +134 (3.40) -199 (5.05) -227 (5.77) 59 +048 (1.22) -241 (6.12) -141 (3.58) 60 -048 (1.22) -241 (6.12) -048 (1.22) 61 -134 (3.40) -199 (5.05) +048 (1.22) 61 -134 (3.53) +139 (3.53) +141 (3.58) 63 -237 (6.02) -048 (1.22) +227 (5.77) 64 -237 (6.02) -048 (1.22) +227 (5.77) 64 -237 (6.02) +048 (1.22) +302 (7.67) 65 -208 (5.28) +139 (3.53) +342 (2.19) 66 -134 (3.40) +199 (5.05) +404 (10.20) 67 -048 (1.22) +146 (3.71) +404 (10.20) 67 -048 (1.22) +146 (3.71) +222 (6.18) +008 (1.22) +146 (3.71) +322 (0.20) 69 +.125 (3.18) +000 (0.29)				SOURIAU shall not be lia due to a use of the Pr	
73	$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$	+280 (7.11) 71 +.125 (3.18) 090 (2.29) +220 (5.59) 72 +.048 (1.22) 146 (3.71) +.141 (3.58) 73 048 (1.22) 146 (3.71) +.044 (1.22) 74 125 (3.18) 090 (2.29) 048 (1.22) 74 125 (3.18) +.000 (0.00) 141 (3.58) 76 125 (3.18) +.000 (0.00) 141 (3.58) 76 125 (3.18) +.000 (0.00) 141 (3.58) 76 125 (3.18) +.000 (0.00) 141 (3.58) 76 125 (3.18) +.000 (0.00) 141 (3.58) 76 125 (3.18) +.000 (0.29) 220 (5.59) 77 +.000 (0.00) +.053 (1.35) 280 (7.11) 78 +.048 (1.22) 029 (0.74) 322 (8.18) 79 044 (1.22) 029 (0.74) 347 (8.81) Applicable to MIL-DTL-38999 only)				the Specifications issued b (professional reco PN: 8[oy either commenda
					ISS DATE Designed By:	Date:	
_					SCALE NA	Gene Tole	Alumir eral linear erances: ±
					FORMAT A3	SOL	RIAU.(JRIAU 521W
l	Н	G	F	E	D	C C	
					•		

σ	⊳				
		4			
		3			
any non-conformit which does not co of the Parties or b dation, technical n	mply with by a third party				
Intry Jurisd	liction & Control List Not Listed	2			
1W35BB					
	MOD N	,			
	CUSTOMER DRAWING				
ninium Plug 8D series					
ar	NPRDS / PROJECT				
	859 This document is the property of	1			
I.COM	SOURIAU it must not be reproduced or communicated without permission				
U DRG N°	SHEET				
W35BB-C	2/2				
В	A				