

building a smarter, unified business foundation

UNITED STATES [CHANGE] ENGLISH REGISTER / LOG IN FOLLOW US



SOLUTIONS PRODUCTS AND SERVICES SUPPORT ABOUT US

Search Panduit.com Subm



Search within category

BUY NOW

DESIGN / INSTALL



LCDN1/0-14DF-X

Two-hole, standard barrel with window, narrow tongue lug, 1/0 AWG wire, 1/4" stud hole, 1" hole spacing, 90° angle tongue.

Specs Documents

★ Add to Favorites

🛒 Add to BOM

RoHS Compliancy Status	Compliant
Material	Tin-Plated Copper
UL Listed	Yes
CSA Certified	Yes
Length (mm)	62.2
Length (In.)	2.45
Copper Conductor Size	1/0 AWG
Stud Hole Size (In.)	1/4
Stud Hole Spacing (In.)	1.00
Tongue Width (In.)	0.52
Barrel Length (In.)	0.94
Wire Strip Length (mm)	25.4
Tongue Thickness	0.13
CE Compliant	No
Wire Strip Length (In.)	1
Barrel Style	Standard
Panduit Color Code	Pink
Product Type	Compression Connectors - Lugs
Angle	90°
Panduit Die Index No.	P42
Tongue Type	Narrow
Stud Hole Size (mm)	6.4
Min. Order Qty.	1.0000
Burndy Die Index No.	12
T&B Die Index No.	42