Characteristics Subardiard Based on ML DT. 38995 Series II Subardiard Based on ML DT. 38995 Series III Subardiard Based on Subard Dr. 38905 Series III Subardiard Based on Subard Dr. 38905 Series III Subardiard Based Control Ust Durability To Subardiard Scottard Lists Subardiard Based Control Ust Durability To Subardiard Scottard Lists Subardiard Based Control Ust Subardiard Based Control Ust Durability To Subardiard Scottard Lists Subardiard Based Control Ust Subardiard Based Control Ust	Г	т <u>0</u> т		0	σ		
Characteristics Sundard: Based on ML DT. 38995 Series II Sundard: Based on ML DT. 38995 Series III Sundard: Based on Sundard State III Ourability : State State Cooper Alloy 0.8µm minimum Durability : State State III Ourability : State State III Sundard: Based on ML DT. 38806 Sundard: Based on Sundard State III Sundard: Based on Sundard State III Sundard: Based State III Sundard: Based State IIII (State IIII) Sundard: Based State IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	4						4
CHARACTERISTICS Standard: Based on MIL DTL 38999 Series III Shell Material :: Aluminium: Shell Material :: Black Zinc Nickel - Instantiation: Copper Alloy Seals & Grommet:: Silicon Elastomer - Orntact Planng:: Gold over copper Alloy 0.8µm minimum - Orntact Planng:: Gold over copper Alloy 0.8µm minimum - Orntact Planng:: Gold over copper Alloy 0.8µm minimum - Orntact Planng:: Gold over copper Alloy 0.8µm minimum - Orntact Planng:: Gold over copper Alloy 0.8µm minimum - Orntact Planng:: Gold over copper Alloy 0.8µm minimum - Orntact Planng:: Gold over copper Alloy 0.8µm minimum - Orntact Planng:: Gold over copper Alloy 0.8µm minimum - Delevered with Souriau contacts and Accessories - Temperature Range:: GoSC to +175°C: - Sait Spray :: 500 hours BASIC SERIES::: 8B:: B:: BASIC SERIES:: 8B:: Basic Series: B:: SHELL TYPE:: In line Receptade OPIC/VENDIDUO Connection: OPIC/VENDIDUO The decomets: Basic Series: B:: Basic Series: B:: Basic Series: B:: Basic Series: B::	ω			LAYOUT SHO	WN AS EXAMPLE		3
CHARCTERISTICS Standard: Based on MIL-DT-38999 Series III Shell Material : Aluminium Shell Material : Aluminium Shell Material : Aluminium Shell Material : Black Zinc Nickel Insulator : Thermoplastic Contacts : Copper Allay Seads & Grommet : Slicon Elastomer - Oritical Material		Koving Shown as overalle					
- Standard : Based on MIL-DTL-38999 Series II Dimetudo Minibidit - Shell Material : Aluminium - Shell Material : Contacts - Contacts : Contacts - Contact Station Sized Weither Offen Station Sized : Contact Material Notice - Contact Material : Sold over copper Alloy 0.8µm minimum - Delivered with Souriau contacts and Accessories : Contact Station Sized Weither Offen Station - Delivered with Souriau contacts and Accessories : Souriau Contacts and Accessories - Temperature Range : 65°C to +175°C - Salt Spray : Sou hours Basic SERIES: 80 1 12 08 8 SHELL TYPE : In line Receptade In line Receptade In the property of OWNOTIFIE In line Receptade In the property of							
Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Contacts : Copper Alloy -Seals & Grommet : Slicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : Sold Aver copper Alloy 0.8µm minimum -Durability : Sold Aver copper Alloy 0.8µm minimum -Durability : Sold over copper Alloy 0.8µm minimum -Durability : Sold Aver copper Alloy 0.8µm minimum -Delivered with Souriau contacts and Accessories - -Temperature Range : 65°C to +175°C -Salt Spray : Sold hours BASIC SERIES: 8D 1 SHELL TYPE : In line Receptacle - SHEL TYPE : In line Receptacle - SHEL TYPE : In line Receptacle -<		-Standard : Based on MIL-DTL-38999 Series III Dim Nominal					
-Durability : 500 Mating cycles Delivered with Souriau contacts and Accessories -Temperature Range : 65°C to +175°C -Salt Spray : 500 hours A 24-09-2016 First Release ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING ITTLE Aluminium Inline plug 8D series SHELL TYPE SHELL TYPE SHELL TYPE SHELL TYPE SHELL TYPE In in Receptacle CONTACT DIF ONENTATION IS		-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer		due to a use of the Pro the Specifications issued by	oducts which does not com either of the Parties or by mmendation, technical no Country Jurisdie	nply with y a third party otice.) ction & Control List	
-Salt Spray : 500 hours A 24-09-2016 ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING BASIC SERIES: 8D SHELL TYPE In line Receptacle SHELL TYPE In line Receptacle CONTACT DNE State	N	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8[Not Listed	2
BASIC SERIES: 8D 1 - 17 Z 08 B B Image: Contract processing contract procesent procesent procesent processing contract procesent processing			A 24-09	9-2016 First Release			
BASIC SERIES: 8D 1 - 17 Z 08 B B B Image: Single sin							<u>N°</u>
BASIC SERIES. SD I					ninium Inline plug		
	→				ances:	859	1
it must not be reproduced or			— SUURI	SOURIAU WWW.SOURIAU.COM		SOURIAU it must not be reproduced or	
SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings) communicated without permission PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 17-08 FORMAT SOURIAU DRG N° SHEET							
PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 17-08 FORMAT SOURIAU DRG N° SHEET A3 8D117Z08BB-C 1/2		CUNTACT LAYOUT:1	-00				
H G F E D C B A	L	H G F E	D			A]

_	Т	۵	г П	m	D	0	
		Contact Layout					
4	-x ($ \begin{array}{c} & & & & & \\ & & & & \\ & & & & \\ & & & &$					
	Conti positio A B C C D D E F	Contacts (Insert arrangement 17-8) Act Location X-axis Y-axis (mm) + 000 (0.00) + 236 (5.99) + 128 (3.25) +.086 (2.18) + 230 (5.84) 078 (1.98) + 0.94 (2.39) 216 (5.49) - 0.230 (5.84) 078 (1.98)					
ω	Shell Arrangement Nu size no. cc 17 -8						
	_						
						SOURIAU shall not be liable f due to a use of the Produc the Specifications issued by eit (professional recomm	icts w ther c
N						PN: 8D1	Count FR
					ISS DATE	16 First Release Latest modification - by	
					Designed By:	Date:	niur
-					SCALE NA	General lir Tolerance ±	
					SOURIA	U WWW.SOURIA	<i>\</i> U.(
					FORMAT A3	SOURI 8D11	
L	Н	G	F	E	D	C	

Φ						
		4				
		3				
any non-conformi which does not co r of the Parties or dation, technical n ntry Juriso R 7ZO8BB	omply with by a third party	2				
	MOD N° CUSTOMER DRAWING					
um Inline plug 8D series						
r	NPRDS / PROJECT 859 This document is the property of					
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
U DRG N° Z08BB-C	SHEET 2/2					
B	A	J				