



Remark:
1. VSWR 1.3 Max up to 6 GHz

Recommended
Cable Stripping Dim's

- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
 2. Thin Gold over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 3. Beryllium Copper
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 5. Teflon
 6. Passivated

RoHS Compliant

Crimped Ferrule
Hex Crimp Size .213 (5.41)

					Dimensions are in Inches				Part No.		NTE Electronics		
					Unless Otherwise Specified Tolerances				Approved				Title
7	Ferrule	Copper	Note 2	1		0.5-6	= ±0.2			Date	4-19-2013	SMA Reverse Polarity Crimp Plug (For RG-58, 58A, 58C, 141, LMR195)	
6	Contact Pin	Note 3	Note 4	1		6-30	= ±0.4			Date	4-19-2013	Drawing No. 06-S002	
5	Gasket	Silicone	Red	1		120-315	= ±1			Date	4-19-2013	File No.	
4	Retaining Ring	SUS 304	Note 6	1		315-1000	= ±1.6			Date	4-19-2013		
3	Insulator	Note 5	Natural	1		1000-2000	= ±2.4						
2	Body	Note 1	Note 2	1									
1	Shell	Note 1	Note 2	1									
No.	Description	Material	Finish	Q'ty	Drawing No.	Scale	4/1	Issue	A				