

## Specification Sheet

Part Number: T150L2X2



Heavy Duty Cable Tie, 32.3" Long, UL Rated, 175lb Tensile Strength, PA66, Red, 25/pkg

Article Number	111-15407
Type	T150L
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none"><li>•Engineered and manufactured for maximum performance and quality.</li><li>•Made from 100% high-quality plastic to ensure efficient recycling.</li><li>•Inside serration for a strong grip onto bundles.</li><li>•Easy application either manually or with a tensioning tool.</li><li>•Bent tail allows for simpler insertion.</li></ul>
Quantity Per	bag

### Product Description

Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Heavy Duty Cable Tie, 32.3" Long, UL Rated, 175lb Tensile Strength, PA66, Red, 25/pkg
<b>Global Part Name</b>	T150L-PA66-RD
<b>Minimum Tensile Strength (Imperial)</b>	175.0
<b>Minimum Tensile Strength (Metric)</b>	780.0
<b>Length L (Imperial)</b>	32.3
<b>Length L (Metric)</b>	820.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.35
<b>Width W (Metric)</b>	8.9
<b>Bundle Diameter Min (Imperial)</b>	0.32
<b>Bundle Diameter Min (Metric)</b>	8.0
<b>Bundle Diameter Max (Imperial)</b>	9.6
<b>Bundle Diameter Max (Metric)</b>	243.8

<b>Thickness T (Metric)</b>	1.9
-----------------------------	-----

<b>Material</b>	Polyamide 6.6 (PA66)
-----------------	----------------------

<b>Material Shortcut</b>	PA66
--------------------------	------

<b>US MIL SPEC</b>	MS3367-6-2	<b>Flammability</b>
--------------------	------------	---------------------

UL 94 V2	<b>Halogen free</b>
----------	---------------------

Yes	<b>Operating Temperature (Metric)</b>
-----	---------------------------------------

-40°F to +185°F (-40°C to +85°C)	<b>ROHS Complaint</b>
----------------------------------	-----------------------

Yes	<b>Certification/Specification WEB</b>
-----	--

UL-ZODZ2.E64139	<b>UL Recognized (US)</b>
-----------------	---------------------------

Yes	<b>UL Recognized (US and Canada)</b>
-----	--------------------------------------

Yes	
-----	--

<b>Package Quantity(Imperial)</b>	25
-----------------------------------	----

<b>Package Quantity (Metric)</b>	25
----------------------------------	----

<b>Customs Number</b>	3926909988
-----------------------	------------

---

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)