	F	T	G	П	m		כ	C	œ	A		_
CHARACTERISTIC Standard : Based on MIL-DTL-38999 Series II Schell Material :: Autminium Schell Kommet:: Schell Kommet:: Schell Kommet:: Schell Kommet:: Schell Kommet:: Schell Kommet:: Oursbillity ::::::::::::::::::::::::::::::::::::		22.6 Max	N Thread		S				SHOWN AS EXAMPLE			4
Shell Material : Aluminitum Shell Material : Aluminitum Shell Material : Nickel - Insulator : Nickel - Insulator : Coper Alloy Scale & Grommet : Silicon Elastomer - Contact Plating : Gold over copper Alloy OBJam minimum - Delivered with Souriau contacts and Accessories			es III	Keying Shown a	Connector dimension							
-Salt Spray : 48 hours -Mass : 20.65 g ± 10% BASIC SERIES: 8D 8D 7 11 F 98 0 0 0	N	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastome-Contact Plating: Gold over copper-Durability: 500 Mating cycle	er er Alloy 0.8µm minimum les		B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1			due to a use of th the Specifications issue (professional	e Products which does not con ed by either of the Parties or b recommendation, technical no Country Jurisdia FR	nply with y a third party tice.) ction & Control List		2
BASIC SERIES: 8D 7 11 F 98 S D SHELL TYPE Jam nut Receptacle SCALE General linear NPRDS / PROJECT 859 1 CONTACT TYPE Standard Crimp Contact ORIENTATION : D SOURIAU Souract BSOURIAU This document is the property of souract Souract <th< td=""><td></td><td>-Salt Spray : 48 hours</td><td>c</td><td></td><td></td><td></td><td>ISS DATE</td><td>Latest modification - b</td><td>у</td><td>CUSTOMER DRAWING</td><td>MOD N°</td><td></td></th<>		-Salt Spray : 48 hours	c				ISS DATE	Latest modification - b	у	CUSTOMER DRAWING	MOD N°	
SHELL TYPE : Jam nut Receptacle NA ± 859 CONTACT TYPE : Standard Crimp Contact ORIENTATION : D NA ± This document is the property of SOURIAU SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) It must not be reproduced or communicated without permission It must not be reproduced or communicated without permission PLATING : F = Nickel CONTACT LAYOUT : 11-98 FORMAT SOURIAU DRG N° SHEET A3 8D711F98SD-C 1/2		BASIC SERIES: 8D	7 - 11 F	98 S D					eneral linear	NPRDS / PROJECT		
A3 SOORIAO DRG N 1/2	→	CONTACT TYPE : Standard Crimp Conta	act						±	This document is the pro SOURIAU it must not be reprodu	ced or	1
		PLATING : F = Nickel	G	F		Г:11-98	A3			Δ		

Г	I G	т (г		0	œ	A
4	Contact Layout $\xrightarrow{A \oplus } \\ \xrightarrow{B \oplus } \\ \xrightarrow{E \oplus } $			Panel cutout JAM NUT RECEPTACLE (TYPE 7)	 С	4
_	Contact position ID Contact location A +.000 (0.00) +.130 (3.30) B +.130 (3.30) +.000 (0.00) C +.065 (1.65) 113 (2.87) D 065 (1.65) 113 (2.87) E 130 (3.30) +.000 (0.00) F +.000 (0.00) 000 (0.00) Shell Arrangement Number of contacts Size Service rating Contact location 11 98 6 20 I All MS20050-98			ØC	<u></u>	
ယ				Dim Nominal B 19.59+0/-0.3 ØC 20.96+0.25/		3
				due to a use of the Pro- the Specifications issued by	e for any non-conformity or damage ducts which does not comply with either of the Parties or by a third party mendation, technical notice.)	
N					Country Jurisdiction & Control FR Not Listed	2
			ISS Designed B		сизтомея р ninium Receptacle 8D series	
			SCALE NA SOU	RIAU WWW.SOUR	IAU.COM it must no	
	H G	F E	FORMAT A3 D	3001	RIAU DRG N° 711F98SD-C B	SHEET 2/2 A