

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
<b>APPLICABLE STANDARD</b>									
<b>RATING</b>	OPERATING TEMPERATURE RANGE	-35 °C TO +85 °C(NOTE1)			STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C(NOTE3)			
	OPERATING MOISTURE RANGE	20 %TO 80 %(NOTE2)			STORAGE MOISTURE RANGE	40 %TO 70 %(NOTE3)			
	CURRENT	1 A			VOLTAGE	150 V AC(DC)			
<b>SPECIFICATIONS</b>									
<b>ITEM</b>		<b>TEST METHOD</b>			<b>REQUIREMENTS</b>			<b>QT</b>   <b>AT</b>	
<b>CONSTRUCTION</b>									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			×   ×	
MARKING		CONFIRMED VISUALLY.						×   ×	
<b>ELECTRIC CHARACTERISTICS</b>									
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).			30 mΩ MAX.			×   —	
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.		20 mV MAX, 1mA(DC OR 1000 Hz)						×   —	
INSULATION RESISTANCE		100 V DC.			500 MΩ MIN.			×   —	
VOLTAGE PROOF		500 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.			×   —	
<b>MECHANICAL CHARACTERISTICS</b>									
MECHANICAL OPERATION		50 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			×   —	
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 1 μs.			×   —	
SHOCK		490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.			② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			×   —	
<b>ENVIRONMENTAL CHARACTERISTICS</b>									
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 →5 TO 35→+85 →5 TO 35°C TIME 30 →10 TO 15 →30 →10 TO 15min UNDER 5 CYCLES.			① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN.			×   —	
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 ~ 95 %, 96 h.			③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			×   —	
RESISTANCE TO SOLDERING HEAT		(1) REFLOW SOLDERING 《REFLOW AREA》 MAX 250°C WITHIN 10 sec. MIN 220°C WITHIN 70 sec 《PREHEATING AREA》 150°C to 160 °C 60 sec. To 120 sec. PUT THROUGH IN REFLOW FUMACE TWICE. LEAVE IN AMBIENT TEMPERATURE AND HUMIDITY FOR 1 HOUR. CONNECTOR TEMPERATURE TO BE AMBIENT FOR SECOND REFLOW. 2) MANUAL SOLDERING SOLDERING IRON TEMPERATURE 350±5°C, FOR 5±1 sec. NO STRENGTH ON CONTACT.			NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.			×   —	
SOLDERABILITY		SOLDERING TEMPERATURE : 235±5°C DURATION OF IMMERSION :			A NEW UNIFORM COATING OF SOLDER SHALL COVER MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.			×   —	
REMARKS				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
NOTE1:INCLUDING THE TEMPERATURE RISE BY CURRENT. NOTE2:NON-CONDENSING NOTE3:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD, AFTER PCB BOARD,OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION.				<i>J. Denferyu</i> '03.03.05	<i>J. Denferyu</i> '03.03.05	<i>J. Miyazaki</i> '03.03.05	<i>J. Miyazaki</i> '03.03.05		
Unless otherwise specified, refer to JIS C 5402									
Note QT:Qualification Test AT:Assurance Test ×:Applicable Test									
<b>HRS HIROSE ELECTRIC CO., LTD.</b>				<b>SPECIFICATION SHEET</b>			PART NO. DF14H-30P-1.25H(56)		
CODE NO.(OLD) CL		DRAWING NO. ELC4-161484-02		PART NO. CL538-0188-0-56				1/1	

TO

