| | т Q Т | | | | | |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
| 4 | Z D D D D D D D D D D D D D D D D D D D | | | | | |
| ω | | LAYOUT SHOWN AS EXAMPLE | | | | |
| | Keying Shown as example | | | | | |
| | CHARACTERISTICS Connector dimension | | | | | |
| - | -Standard : Based on MIL-DTL-38999 Series III Dim Nominal ØS 35.7 Max | | | | | |
| | -Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer | SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) | | | | |
| N | -Contact Plating : Gold over copper Alloy 0.8µm minimum | CountryJurisdiction & Control ListFRNot Listed2 | | | | |
| | -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories | PN: 8D517F06BD | | | | |
| | -Temperature Range : -65°C to +200°C -Salt Spray : 48 hours | A 14-10-2016 First Release | | | | |
| _ | -Mass : 39.5 g ± 10% | ISS DATE Latest modification - by MOD N° | | | | |
| | | Designed By: Date: CUSTOMER DRAWING | | | | |
| | | TITLE Aluminium Plug 8D series | | | | |
| _ _ | BASIC SERIES: 8D 5 - 17 F 06 B D SHELL TYPE : Plug with RFI Shielding - - 17 F 06 B D | SCALE General linear NPRDS / PROJECT NA ± 859 | | | | |
| | | ATION : D Matings) SOURIAU WWW.SOURIAU.COM Matings) | | | | |
| | PLATING : F = Nickel CONTACT LAYOU | | | | | |
| | | A3 8D517F06BD-C 1/2 | | | | |
| | H G F E | $\begin{array}{c c c c c c c c c c c c c c c c c c c $ | | | | |

| | | | G | гт | т | | D | 0 | |
|---|--------------------------|-------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---|--------------|--------------------------------|-------------------------------------------------------------------------------|-----------------------------------|
| | | Contac | ct Layout | | | | | | |
| 4 | | -x (D + F | + Y A ⊕ ⊕ B + Y + × + × | | | | | | |
| | | Contact Contact | €Y ntacts ngement 17-6) Location | | | | | | |
| ယ | Shell Arra size 17 | A + 121 B + 241 C + .000 D241 E121 F + .000 no. contacts co | m) (mm) (3.07) + 209 (5.31) (6.12) + 000 (0.00) (0.00) - 241 (6.12) (6.12) + 000 (0.00) (3.07) + 209 (5.31) (0.00) + 000 (0.00) Size Service Contact Superint ntacts rating location | sedes 053-6 | | | | | |
| | | | | | | | | SOURIAU shall not be li due to a use of the P the Specifications issued | roducts w |
| S | | | | | | | | (professional rec | |
| | | | | | | | ISS DAT | | D517 |
| | | | | | | | Designed By: TITLE SCALE | Gen | Alumir eral linear erances: |
| | | | | | | | SOURIA | | ± |
| | | I | | | | | FORMAT A3 | 80 | JRIAU 0517F |
| | Н | | G | F | E | \mathbf{V} | D | C | |

