		т	Q	нт —	m	1		0	Ξ	Þ		7
Concertor dimension Submarketial Sheard Art Stacks on NUL DTL 3899 Series II Sheard Art Stacks on NUL DTL 3899 Series II Sheard Art Stacks on NUL DTL 3899 Series II Sheard Art Stacks on NUL DTL 3899 Series II Sheard Art Stacks on NUL DTL 3899 Series II Sheard Art Stacks on Thermologistic Sheard Art Stacks on Thermologistic Soutact Plaining Sold Over cooper Alloy OSymmininum Soutact Plaining Sold Over cooper Alloy OSymmininum Soutact Plaining Sold Over cooper Alloy OSymmininum Ouring Contact Plaining Sold Over cooper Alloy OSymmininum Soutact Plaining Sold Over cooper Alloy OSymmininum Believered with Souriau contacts and Accessories Physics Sold Over cooper Alloy OSymmininum Mass Soutact Plaining Sout Sold Over Cooper Alloy OSymmininum Spring Try Souta Over	4		S É	ØS								4
CHARACTERISTICS Standard : Based on MIL-DTL-38999 Series II Shell Material : Aluminium Shell Material : Shuminium Shell Plating : Olive drab Cadmium Shell Plating : Olive drab Cadmium Shell Material : Shell Plating : Olive drab Cadmium Social Plating : Gold ver copper Alloy Os Jum minimum Social Plating : Gold ver copper Alloy Os Jum minimum - Ourshill ty :: Soo Mating cycles - Ourshill ty :: Soo Mating cycles - Ourshill ty :: Soo Mating cycles - Mass :: 17.15 g ± 10% BASIC SERIES: Soo 5 11 W Q2 B E BASIC SERIES: Soo 5 11 W Q2 B E BASIC SERIES: Soo 5 11 W Q2 B E BASIC SERIES: Soo 5 11 W Q2 B E BELETTYPE : Flug with RFI Shielding Social Chairing Context : CONTACT TYPE : Standard Crimp Context 11 W Q2 B E BELETTYPE : Standard Crimp Context NPROS / PROJECT Social Real Control Context Social Real Context Conte	ω							LAYOUT SHOWN	AS EXAMPLE			3
-Standard : Based on MIL-DTL-38999 Series III Dim Control Milector Million -Shell Material : Aluminium -Shell Material : Aluminium -Shell Matring : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Matring : Gold over copper Alloy 0.8µm minimum -Outered With Souriau contacts and Accessories				Keying Sho	own as example							
- Standard : Based on MIL-DTI-38999 Series III - Shell Matrial : Aluminium - Shell Matrial : Aluminium - Shell Matrial : Aluminium - Shell Matrial : Comper Alloy - Contact : Cooper Alloy - Seals & Grommet : Silicon Elastomer - Contact Plaing : Gold over coper Alloy 0.8µm minimum - Octicat Plaing : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum - Outling : Gold over coper Alloy 0.8µm minimum	c	CHARACTERISTICS			Connector di	mension						
- Shell National ∴ Additional - Shell National ∴ Olive drab Cadmium - Shell National ∴ Olive drab Cadmium - Shell National ∴ Olive drab Cadmium - Insulator ∴ Thermoplastic - Contacts : Copper Alloy - Seels & Grommet : Silloon Elastomer - Contact Plaining : Gold over copper Alloy 0.8µm minimum - Ourability : Sou Nating cycles - Delivered with Souriau contacts and Accessories - On tacts - Temperature Range : 65°C to +175°C - Salt Spray : Sou Nating cycles - Mass : 17.15 g ± 10% Basic SERIES: 8D 5 SHELL TYPE : Rug with RFI Shielding CONTACT TYPE : Standard Crimp Contact ORIENTATION :: CORIENTATION ::	-:	-Standard : Based on MII	L-DTL-38999 Series III		Dim	Nominal						
 -Contact Plating :: Gold over copper Alloy 0.8µm minimum -Durability :: 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range :: -65°C to +175°C -Saft Spray :: 500 hours -Mass :: 17.15 g ± 10% BASIC SERIES: 8D 5 - 11 W 02 B E BASIC SERIES: 8D 5 - 11 W 02 B E General linear Tolerances: 859 ±- NPRDS / PROJECT Tolerances: 859 ±- This document is the property of SOURIAU.COM This document is the property of SOURIAU.COM 		-Shell Plating -Insulator -Contacts	: Olive drab Cadmium : Thermoplastic : Copper Alloy		Z	31 Max		due to a use of the Produc the Specifications issued by eith (professional recomme	ts which does not compl her of the Parties or by a endation, technical notic	ly with third party e.)		
-Delivered with Souriau contacts and Accessories -Temperature Range :: -65°C to +175°C -Sait Spray :: 500 hours -Mass :: 17.15 g ± 10% BASIC SERIES:: 8D 5 - 11 W 02 B E SHELL TYPE :: Plug with RFI Shielding CONTACT TYPE :: Standard Crimp Contact ORIENTATION :: E PN: 8D511W02BE A 17-10-2016 First Release A 17-10-2016 First Release A 17-10-2016 First Release MOD N* Designed By: Date: CUSTOMER DRAWING SURIAU WWW.SOURIAU.COM This document is the property of souristic train th	-	-	: Gold over copper Alloy 0.8µm mini	mum			[2
- Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 17.15 g ± 10% BASIC SERIES: 8D 5 - 11 W 02 B E SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact III W 02 B E CONTACT TYPE : Standard Crimp Contact III W 02 B E ORIENTATION : E ORIENTATION : E												
-Salt Spray :: 500 hours -Mass :: 17.15 g ± 10% BASIC SERIES: 8D 5 - 11 W 02 B E CONTACT TYPE :: Standard Crimp Contact U CONTACT TYPE U CONTACT TYPE :: Standard Crimp Contact U CONTACT TYPE U CONTACT												
- Mass : 17.15 g ± 10% - Mass : DATE Latest modification - by Date: CUSTOMER DRAWING - Designed By: Date: CUSTOMER DRAWING - Date: CUSTOMER DRAWING - Date: CUSTOMER DRAWING - Mass : Date: CUSTOMER DRAWING - SCALE NA							A 17-10-2016	First Release				
Designed By: Date: CUSTOMER DRAWING BASIC SERIES: 8D 5 - 11 W 02 B E SHELL TYPE : Plug with RFI Shielding SCALE NA SCALE NPRDS / PROJECT CONTACT TYPE : Standard Crimp Contact ORIENTATION : E ORIENTATION : E SOURIAU This document is the property of SOURIAU.COM SOURIAU it must not be reproduced or							ISS DATE	Latest modification - by			MOD N°	
BASIC SERIES: 8D 5 - 11 W 02 B E SCALE Tolerances: B <			0				Designed By:	Date:	С	USTOMER DRAWING		
A SHELL TYPE : Plug with RFI Shielding III W 02 B E E BILL TYPE : Plug with RFI Shielding NA Tolerances: ± 859 CONTACT TYPE : Standard Crimp Contact ORIENTATION : E BILL TYPE : Standard Crimp Contact This document is the property of SOURIAU it must not be reproduced or							TITLE	Aluminium Plug 8D series				
CONTACT TYPE : Standard Crimp Contact ORIENTATION : E SOURIAU WWW.SOURIAU.COM It must not be reproduced or	-			1 W 02 B E			-					-
SOURIAU WWW.SOURIAU.COM it must not be reproduced or	-	CONTACT TYPE : Standard Crimp Contact ORIENTATION : E								perty of	1.	
	-				CONTACT		SOURIAU	WWW.SOURIA	J.COM	it must not be reprodu		
PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 11-02 FORMAT SOURIAU DRG N° SHEET	-		live drah Cadmium	┙ │ └──	CONTACT		FORMAT					_
A3 8D511W02BE-C 1/2	-			I								
H G F E D C B A			C							٨		

r	Ŧ	ര	т	m	D	0
		Contact Layout				
4	.x .0 (2)	+Y IB IA +X 95 -Y .095 (2.4 imm)				
	Cont positi ID A B Sheli Arrangement size no. 11 -2	X-axis Y-axis (mm) (mm) + -0.95 (2.41) 095 (2.41) +.000 (.00)				
ω						
	+					SOURIAU shall not be liable for due to a use of the Products the Specifications issued by eithe (professional recommen
N						PN: 8D51
					A 17-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
_					TITLE SCALE NA	Alum General linea Tolerances:
					SOURIA	
				_	FORMAT A3	SOURIA 8D511
l	Н	G	F	E	D	С

