Σ Ω Π Μ		0	□ >	•]
					4
					3
		LAYOUT SHOWN AS EXAN	1PLE		
Keying Shown as example					
CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal					
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Material : Aluminium					
-Shell Plating : Nickel Z 31 Max VV THREAD M25x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with			
-Insulator : Thermoplastic		the Specifications issued by either of the Parties or by a third party			
-Contacts : Copper Alloy		(professional recommendation	, technical notice.)		
-Seals & Grommet : Silicon Elastomer		Country Jurisdiction & Control List			
Contact Plating : Gold over copper Alloy 0.8μm minimum					2
-Durability : 500 Mating cycles					
-Delivered with Souriau contacts and Accessories		PN: 8D517F26SN			
-Temperature Range -65°C to +200°C	A 14-10-2016	First Release			-
-Salt Spray : 48 hours					
	ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	-
	TITLE	Aluminium Plug 8D series			
	SCALE				_
BASIC SERIES: 8D 5 - 17 F 26 S N → SHELL TYPE : Plug with RFI Shielding - 17 F 26 S N	NA	General linear Tolerances:	NPRDS / PROJECT 859		4
			This document is the p	roperty of	- '
CONTACT TYPE : Standard Crimp Contact ORIENTATIO SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Mat	- SUURIAU	SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or communicated without permission			
				SHEET	_
PLATING : F = Nickel CONTACT LAYOUT : 1	A3	SOURIAU D		1/2	
		8D517F26			
H I G I F I E	D	C	B I A	l i i i i i i i i i i i i i i i i i i i	

