

## Support bracket - AB-SK-D TOP INSULATED - 3062087

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Support bracket, Bracket for busbars, set every 20 cm, Length: 155.8 mm, Width: 5.2 mm, Color: gray



### Product Features

- For mounting SK and SKS shield connection clamps
- Can be labeled with zack marker strip and KLM terminal strip markers
- Compact design with 5.2 mm pitch
- Parking option for bridges and plugs
- The 3 x 10 mm rail can be mounted in the supports vertically, horizontally, and at a 45° angle for optimum conductor placement
- For user-friendly shield connection, especially for single and multi-level terminal blocks and devices with a front connection



### Key commercial data

Packing unit	1 PCE
Minimum order quantity	10 PCE
Custom tariff number	85472000
Country of origin	China

### Technical data

#### Dimensions

Length (b)	155.8 mm
Width (a)	5.2 mm

#### General

Color	gray
Inflammability class according to UL 94	V0
Material	PA

# Support bracket - AB-SK-D TOP INSULATED - 3062087

## Classifications

eCl@ss

eCl@ss 4.0	23150301
eCl@ss 4.1	23150301
eCl@ss 5.0	27141143
eCl@ss 5.1	27141143
eCl@ss 6.0	27400607
eCl@ss 7.0	27400607
eCl@ss 8.0	27400607

## ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC000483
ETIM 5.0	EC001166

## UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708
UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121708

## Drawings

Dimensioned drawing

