

APPLICATOR PARTS LIST

TYPE  
INSULATION PENETRATING  
SIDEWISE LUG

AMP INCORPORATED  
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.
1	WIRE CRIMPER		
2	INS. CRIMPER 453901-2	1	<del>565002-0</del>
3	ANVIL	1	465526-6
4	ANVIL SPACER	1	810070-4
5	SHEAR BLADE		
6	REAR SHEAR PLATE		
7	REAR ANVIL SPACER Rear Pl.	1	811959-5
8	FRONT SHEAR PLATE		
9	REAR ANVIL SPACER PLT.		
10	FRONT <del>ANVIL SPACER</del> Strip Holder	1	811593-1
11	TOOL SPACER	1	377132
12	CRIMP SPACER		
13	FRONT STRIP GUIDE	1	386943
14	REAR STRIP GUIDE	1	465110-8
15	RAM	1	471912
16	TOOL HOLDER		
17	ADJ. CRIMP MOUNT		
18	ADJ. BLOCK		
19	APPLICATOR MOUNT ASSY.		
20	BASE PLATE	1	465100
21	BASE BLOCK	1	465101
22	STRIP GUIDE PLATE	1	465114-1
23	ANVIL HOLDER		
24	AUX. ANVIL HOLDER		
25	STRIPPER	1	386361
26	STRIPPER MOUNT	1	386362
27	<del>RETAINER PLATE</del>	<del>1</del>	<del>389078</del>
28	STRIPPER MOUNT BRACKET	1	387715-1
29	STRIPPER BUSHING	1	386368
30	STOCK DRAG	1	386955
31	STOCK DRAG HANDLE		
32	STOCK DRAG STUD 374900	1	<del>370573</del>
33	STOCK DRAG SPRING	1	370572
34	STOCK DRAG ADJ. <del>WASHER</del> Nut	1	21022-3
35	FEED FINGER HOLDER	1	386942
36	FEED FINGER	1	386941
37	FEED FINGER TIP	1	387251
38	FEED FINGER <del>SPACER</del> Guide	1	689915-2
39	BASE CASTING	1	570238
40	GUARD 457665-1	1	<del>811301-1</del>
41	<del>Bracket Guard</del>	<del>1</del>	<del>811301-1</del>

NO.	DESCRIPTION	REQ.	PART NO.
42	Shear Plate (Left)	1	811855-1
43	Shear Block (Right)	1	386372
44	Floating Shear	1	465406
45	Retaining Plate (Front)	1	811714-3
46	Retaining Plate (Rear)	1	810822-1
47	Spring - Shear Return	1	374322
48	Shear Depressor	1	387265
49	Key, Shear Return	1	386358
50	<del>Guard Mt.</del>	<del>1</del>	<del>811306-1</del>
51			
52			
53			
54	Rear Strip Guide Spacer	1	811527-9
55			
56			
57			
58			
59			
60			
61			
62			
63			
64			
65	Tension Adj. Plate	1	374999
MISCELLANEOUS			
66	<del>2" Dia. Steel Support</del>	<del>1</del>	<del>565002-2</del>
67	Lubricator Ass'y.	1	465184-2
68	Oil, Synthetic	1	22014-1
69			
70			
71			
72			

CRIMPING DATA		TERMINALS
TO APPLY TERMINAL		61504-
WIRE SIZE	CRIMP HEIGHT	
CRIMP WIRE	SIZE	TYPE
INSUL.	.062	F
SLEEVED		.290
INSULATION RANGE		WIRE RANGE
.030 - .035		Tinsel
EXPLODED VIEW		
A-6002-4		A-6002-6
REMARKS:		
▲ Mt. on Item 13		
<p><b>THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.</b></p>		
■ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT		
THIS APPLICATOR IS TO BE USED ON		
AMP-O-ELECTRIC 1-471273-3		
AMP-O-ELECTRIC		DIST.
Mech Feed 692110-2		4
SERIAL NO.	DATE SHIPPED	DESIGNED
		R. Bennett
CUSTOMER NAME AND ADDRESS		CHK'D. 2-7-69
		H. Holmbeck
		APP'D.
APPLICATOR NUMBER	REV. F	SHEET
	565950-1	1 OF 1