



Click [here](#) for the 3D model.

Dimensions

| | |
|------|-----------------|
| L | 160mm NOM |
| W | 70mm NOM |
| H | 60mm NOM |
| Lead | Screw Terminals |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Tray, Box |
| Packaging Quantity | 12 |
| Component Weight | 1200 g |

General Information

| | |
|---------------|--------------------------------------|
| Series | LF |
| Style | Metal Box |
| Description | Metal Box |
| Phase | Three-phase |
| RoHS | With Exemptions |
| SCIP Number | 10661cea-adfc-45e6-be80-e6b4fd31a87d |
| Notes | DC Available. |
| Miscellaneous | 30 K Self-Temperature Rise Max. |
| Lead | Screw Terminals |
| Terminal Type | Screw |

Specifications

| | |
|-------------------|--|
| Voltage AC | 250 VAC |
| Voltage | 1500 VAC Withstanding Voltage 1 Min. Line to Ground |
| Rated Current | 20 A (AC/DC) |
| Rated Temperature | 55°C |
| Temperature Range | -20/+55°C |
| Leakage Current | 1 mA MAX (250 V 60 Hz) |
| Resistance | 300 MOhms MIN Insulation 500 VDC 1 Min. Line To Ground |