

	σ		A					
/					4			
AS EX4	AMPLE				3			
s which er of t indation untry FR	non-conformit th does not co he Parties or to on, technical no Jurisd	mply with by a third p otice.)	ontrol List		2			
	1	CUSTON		MOD N°				
ess S	CUSTOMER DRAWING Steel Plug 8D series							
ar :	NPRDS / PROJECT 859							
This document is the property of SOURIAU it must not be reproduced or communicated without permission								
	DRG N° 5AN-C			SHEET 1/2				
	В		А		-			

ſ	Ξ	۵		П	— п	D	0	
4		Contact Layout						
	2 -312 (7.92) 3 -312 (7.92) 4 -242 (6.15) 5 -234 (5.94)	Y-axis (mm) Contact position ID X-axis (mm) Y + 086 (2.18) 29 .000 (0.00) .09 - 0.04 (0.10) 30 .000 (0.00) .78 094 (2.39) 31 .000 (0.00) .27 + .221 (5.61) 32 +.089 (2.26) +.31 + .131 (3.33) 33 +.078 (1.98) +.22 + .041 (1.04) 34 +.078 (1.98) +.13	-axis mm) 4 (2.39) 4 (4.67) 4 (0.60) 6 (8.03) 1 (5.61) 1 (3.33) 1 (1.04)					
ω	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	-139 (3.53) 36 +078 (1.98) -04 -229 (5.82) 37 +078 (1.98) -13 +279 (7.09) 38 +078 (1.98) -22 +176 (4.47) 39 +078 (1.98) -31 +086 (2.18) 40 +172 (4.37) +27 -0.04 (0.10) 41 +156 (3.96) +17 -0.94 (2.39) 42 +156 (3.96) +00 -124 (4.67) 43 +156 (3.96) -00 -274 (6.96) 44 +156 (3.96) -18 +316 (3.03) 45 +156 (3.96) -18 +122 (1.561) 46 +156 (3.96) -27 Contacts (Insert arrangement 17-35) m Location	9 (1.24) 9 (3.53) 9 (5.82) 9 (5.82) 9 (8.10) 9 (7.09) 6 (4.47) 6 (2.18) 4 (0.10) 4 (2.39) 4 (4.67) 4 (6.96)					
	position X-axis ID (mm) 19 -078 (1.98) 20 -078 (1.98) 21 -078 (1.98) 22 -078 (1.98) 23 -078 (1.98) 24 -078 (1.98) 25 .000 (0.00) 26 .000 (0.00) 27 .000 (0.00) 28 .000 (0.00) Shell Arrangement no. Nu	(mm) (mm) (mm) (mm) +131 (3.33) 47 +242 (6.15) +22 +041 (104) 48 +234 (5.94) +13' -049 (124) 49 +234 (5.94) +04' -138' (3.53) 50 +234 (5.94) -049' -239 (5.82) 51 +234 (5.94) -13' -319 (8.10) 52 +234 (5.94) -23' -319 (8.10) 52 +324 (5.94) -23' -319 (8.10) 53 +312 (7.92) -004' +176 (447) 54 +312 (7.92) -004' +086 (2.18) 55 +312 (7.92) -094' -004 (0.10) mber of Size Service Contact Si ontacts contacts rating location Si	axis nm) (15.61) (15.61) (1.64) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (1.24) (due to a the Specificat	hall not be liable for ar use of the Products w ions issued by either o fessional recommenda
N	17 -35	55 22D M Ali M	327529-35					Count FR PN: 8D517
							-10-2016 First Release DATE Latest modific y: Date of the provided states of the provided s	cation - by ate:
_						SCALE NA		General linear Tolerances: ±
						FORMAT A3	RIAU WW	W.SOURIAU. SOURIAU 8D517S
L	Н	G		F	E	D	C	

