



- NOTES
- ① The recommended tightening torque of Ref No. ⑥ : 4 to 4.5 N·m.
 - ② The recommended tightening torque of Ref No. ⑩ : 0.2 to 0.25 N·m.
 - 3 One example of the rotation of REF. No. ⑥ to REF. No. ① is shown.
 - 4 LOCTITE 263 HENKEL JAPAN or equivalent is recommended to prevent REF. No. ①, ⑥ and ⑩ for loosening.
 - 5 This products to be used with cable clamp, JR21WCC-※
 ※Designate diameter(mm) of applicable cable.
 - 6 The cable pull and twisting strength, waterproof tightness and other characteristics may differ,
 depending on the cable structure.
 Please confirm before the use.

5	PHOSPHOR BRONZE	NICKEL PLATING	10	STAINLESS STEEL	HEX SOCKET SET SCREW HEX : 1.27
4	PHENOL FORMALDEHYDE	(BLACK) UL94V-0	9	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)
3	PHENOL FORMALDEHYDE	(BLACK) UL94V-0	8	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)
2	COPPER ALLOY	SILVER PLATING 3μm min	7	BRASS	BLACK CHROME PLATING
1	ALUMINUM ALLOY	BLACK CHROME PLATING	6	BRASS	BLACK CHROME PLATING
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT	DESCRIPTION OF REVISIONS	
DESIGNED		CHECKED		DATE	
APPROVED : HY. KOBAYASHI 18.02.26			DRAWING NO. EDC-110563-31-00		
CHECKED : HY. KOBAYASHI 18.02.26			PART NO. JR21WP-16P(31)		
DESIGNED : TH. KAMEYA 18.02.22			CODE NO. CL114-2006-9-31		
DRAWN : MK. INOUE 18.02.13			1/1		