

Specification Sheet

Part Number: T30R8C2



Standard Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, Gray, 100/pkg

Article Number	116-03018
Type	T30R
Color	Gray (GY)
Features & Benefits	<ul style="list-style-type: none">• Inside serrations allow for strong hold on cables and wire bundles.• Head design provides high tensile strength with very low insertion force.• Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Standard Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, Gray, 100/pkg
Global Part Name	T30R-PA66-GY
Minimum Tensile Strength (Imperial)	30.0
Minimum Tensile Strength (Metric)	135.0
Length L (Imperial)	5.8
Length L (Metric)	148.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.14
Width W (Metric)	3.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.38
Bundle Diameter Max (Metric)	35.0

Thickness T (Metric)

1.1

Material

Polyamide 6.6 (PA66)

Material Shortcut

PA66

US MIL SPEC

SAE-AS33671

MS3367-5-8

Flammability

UL 94 V2

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +185°F (-40°C to +85°C)

ROHS Complaint

Yes

Certification/Specification WEB

CAGE Code 53421 UL-ZODZ.E64139

UL Recognized (US)

Yes

UL Listed (US and Canada)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909987

Content Unit(BMEcat)

pcs.

Weight (Metric)

0.7