

Specification Sheet

Part Number: 170-03024



Braided Sleeving, Split Wrap, .5" Dia, PET, Black, 75 ft/reel

Article Number

170-03024

Type

BSPSW120

Color

Black (BK)

Features & Benefits

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout unrolling.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

Quantity Per

reel

Product Description

A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

Short Description	Braided Sleeving, Split Wrap, .5" Dia, PET, Black, 75 ft/reel
Global Part Name	BSPSW120-PET-BK
Length L (Imperial)	75.0
Length L (Metric)	22.9
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	0.5
Bundle Diameter Max (Metric)	12.7
Diameter D (imperial)	0.50
Diameter D (metric)	12.7
Nominal Diameter (Imperial)	1/2
Nominal Diameter (Metric)	12.7
Wall Thickness WT (Imperial)	0.025
Wall Thickness WT (Metric)	0.64
Material	Polyester (PET)

Material Shortcut

PET

Flammability

UL 94 V0

Halogen free

Yes

Operating Temperature (Metric)

-94°F to +257°F (-70°C to +120°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

UL Recognized (US)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

75

Package Quantity (Metric)

22.86

Customs Number

3926909987

Weight (Metric)

0.48

Weight (Imperial)

1.05