ב בער ביו	m m		0	₿		]
A Z				I A REALIZATION DE LA REALIZ		4
			LAYOUT SHOWN AS EXA	MPLE		3
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	II Material       S       41.7 Max         Z       31 Max         II Plating       Clive drab Cadmium         II Plating       VV THREAD         Material       VV THREAD         Material       VV THREAD         Material       SOURIAU shall not be liable for any non-conformity or damage         due to a use of the Products which does not comply with         due to a use of the Products which does not comply with         the Specifications issued by either of the Parties or by a third party         (professional recommendation, technical notice.)					
<ul> <li>Contact Plating : Gold over copper Alloy 0.8μm minimum</li> </ul>			FR	Not Listed		2
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D521W41SN			
-Temperature Range : -65°C to +175°C						-
-Salt Spray : 500 hours		A 10-10-2016	First Release			
		ISS DATE	Latest modification - by		MOD N°	1
		Designed By:	Date:	CUSTOMER DRAWING		-
		TITLE	TITLE     Aluminium Plug 8D series			
→ BASIC SERIES: 8D 5 - 21 W 41 SHELL TYPE : Plug with RFI Shielding	S N	SCALE NA	General linear Tolerances: ±	NPRDS / PROJECT <b>859</b>		1
CONTACT TYPE : Standard Crimp Contact	ORIENT		WWW.SOURIAU.CO	This document is the pro SOURIAU it must not be reprodu		-
SHELL SIZE : 21	CONTACT TYPE : SOCKET(500			communicated without p		
PLATING : W = Olive drab Cadmium	CONTACT LAYOU		SOURIAU E		SHEET	1
		A3	8D521W4	1SN-C	1/2	
H G	F E	D	С	BA		-

		G	г П	m		0
		Contact Layout				
4		+ Y				
	<	31° 23 31° 41' - 13 HOLES 16° - 20 HOLES				
	Shell Arrangement Num size no. con	Insert arrangement 21-41 iber of Size Service Contact Supersedes tacts contacts rating location	7			
ယ	21 -41 4	41 20 I All MS20055-41	]			
	-					SOURIAU shall not be liable for ar
						due to a use of the Products w the Specifications issued by either c (professional recommenda
						Count
N						FR
						PN: 8D521
					A 10-10-20	116 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
					SCALE	General linear
-					NA	Tolerances:
					SOURIA	U WWW.SOURIAU.
					FORMAT	SOURIAU
	Н	G	F	E	A3	8D521W
	Π		I F			

