


- Notes:**
- A. Material:**
- Housing: PBT WITH G/F30% Color:Black
  - Terminal: COPPER ALLOY, TIN PLATED
- B. Electrical Characteristics:**
- Rating: 15A, 250V ~ (UL, CUL)
  - 10A, 250V ~ (CCC, VDE, SEMKO, NEMKO, FIMKO, DEMKO, SAA)
  - Electric Strength: AC 2,000 V FOR ONE MINUTE
  - Insulation Resistance: 100MΩ MIN, AT 500V DC
- C. Approvals:**
- UL, CUL, CCC, VDE, SEMKO, NEMKO, FIMKO, DEMKO, SAA



**RoHS compliant**

Scale	1:1
TOLERANCE	
X.X	±0.3
X.XX	±0.2
X.XXX	±0.1
DIM	TOL
Ang.	±3°
UNIT	mm

Id.	Modification	Date	Name
①	Drawn	14.12.2007	N.Schulz
②	Update	08.07.2009	Dean
③	Change of plant	17.12.2012	Winnie
④	Alternative	16.01.2017	Winnie
		14.12.2007	N.Schulz

**ASSMANN**  
WSW/ components

Customer-No.	
ASSMANN WSW-No.	A-KGS-F/A
Drawing-No.	ASS 0889A CO
Replace	rev04
SHEET	

1

2

3

4

5

6

7

186