



Features:

- ✓ Allows cables with F style connector to attach quickly and reliably to a BNC connector.
- ✓ Adapter is precision machined (not die-cast) from brass.
- ✓ Adapter utilizes gold plated center contacts for superior signal transfer.

Materials:

| | |
|-----------------|-----------------------------|
| Connector Body: | Nickel plated brass |
| Pin Contact: | Gold plated brass |
| Socket Contact: | Gold plated phosphor bronze |
| Insulator: | PTFE |

Ratings:

| | |
|------------------------|--------------------|
| Impedance: | 75 Ohms |
| Frequency: | 0 to 500 MHz |
| VSWR: | 1.5 max |
| Contact Resistance: | 3 Milliohms max. |
| Voltage: | * 500 V |
| Insulation Resistance: | 5,000 Megohms min. |
| Insertions: | 500 |
| Temperature: | -40 to +65 C |

* *Hands free testing* in controlled voltage environment: *For CE compliance:* not intended for hand held use at voltages above 33 Vrms / 70 Vdc.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 888-403-3360 Technical Assistance: 800-241-2060
For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com