



- NOTES
- ① THE RECOMMENDED TIGHTENING TORQUE REF NO. ① : 6 TO 7 N · m.
THE RECOMMENDED TIGHTENING TORQUE REF NO. ⑤ : 1.2 TO 1.5 N · m.
THE RECOMMENDED ADHESIVE OF REF NO. ① : LOCTITE 242 BY HENKEL JAPAN LTD.
 - ② WATER RESISTANCE, CABLE CLAMP FORCE, CABLE RETENTION FORCE IN AXIAL DIRECTION AND OTHER CHARACTERISTICS COULD VARY DEPENDING ON EACH CABLE CONSTRUCTION.
 - ③ THIS PRODUCT IS DELIVERED DISASSEMBLED.

3	POLYACETAL	(WHITE)					
2	SILICONE RUBBER	(BLACK)	5	STAINLESS STEEL			
1	ALUMINUM ALLOY	NIKEL PLATING	4	STAINLESS STEEL			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 2 : 1	COUNT \triangle	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
HRS HIROSE ELECTRIC CO., LTD.		APPROVED : SU. OBARA	09.10.20	DRAWING NO.	EDC3-115589-00		
		CHECKED : HY. KOBAYASHI	09.10.19	PART NO.	EM35WCC-23		
		DESIGNED : HS. NAGANO	09.10.19	CODE NO.	CL138-0007-0-00		
		DRAWN : HS. NAGANO	09.10.19		\triangle 1/1		