

## Lilliput FA1210/C/T - 12.1" HDMI Capacitive Touch Monitor

Aspect Ratio	4:3
Brightness	800cdm <sup>2</sup>
Contrast Ratio	900:1
Display Screen	12.1"
Resolution	1024 x 768
Touch Panel	Capacitive 10-point
Viewing Angle	170° / 170°
<b>Monitor Specification</b>	
Video Inputs	1x HDMI 1.4b (supports 4K 30Hz), 1x VGA, 1x Mini USB (for Upgrade Only), 1x USB-A (for touch screen)
Audio Outputs	Speaker x 2, Earphone plugs x1
<b>Size</b>	
Dimensions	264.4mm x 224.1mm x 33.4mm
Weight	1.27Kg
<b>Power</b>	
Current	<=1.1A (12V)

Input Voltage	DC 12-24A
Power Consumption	c. 13W
<b>Environment</b>	
Operating Temperature	-30°C to +80°C
Storage Temperature	-30°C to +85°C
Screen Size (diagonal)	10.1 inch
Aspect Ratio	16:10
Native Resolution	1920 x 1200 (native) - 10.1" 8 Bit IPS
Maximum Resolution	1920x1080 (maximum)
Viewing Angle (degrees)	170° x, 170° y
Brightness Ratio (cd/m2)	320
Contrast Ratio	1000:1
Backlight	LED
Video Inputs	HDMI, VGA
Audio Outputs	Internal Speaker, Earphone Jack
Touchscreen Technology	10 Point Capacitive Touchscreen

Input Power	DV 7-24V (12V 1.5A DC Plug provided)
Operating Temperature	0°c to +50° degrees
Mounting Options	VESA 75, ¼ inch BSW thread, vertical slot mount mechanism
<b>Contents of Box</b>	
Product	1 x FA1016-NP/C monitor
Connection Cables	1x HDMI A-A cable, 1x VGA cable
Power Adaptor	1x DC 12V plug (available in UK, US and EU style),
Mounts and stands	Gimbal Bracket (Optional) // VESA 75 Stand (Optional)
<b>Dimensions</b>	
Height (mm)	157
Width (mm)	252
Depth (mm)	25
Weight (g)	560
<b>Environment</b>	
Storage Temperature	-20°c to 60°c