Product NO. BC-202-400				
REV	DESCRIPTION	DWN	DATE	APPROVEN
R1.0	First issue	Gavin	2021/03/09	JIM.KING



Recommended hole size















Specifications
Impedance: 50 Ohms
Frequency Range:0-6G
VSWR:1.5MAX
Working Voltage:1000 VRMS(max at sea level)
Dielectric Withstanding Voltage:1500 vrms(max at sea level)
Insulation Resistance:5000 MOhms min
Durability Mating:500 Cycles min
Temperature Range:-65℃ TO +165℃

No	Connector color
BC-202-400-RD	Body electrophoresis: Red
BC-202-400-BL	Body electrophoresis: Blue
BC-202-400-BK	Body electrophoresis: Black

NO	DESCRIPTION	MATERIAL	FINISH	QTY
7	COPPER TUBE	BRASS	NICKEL	1
6	FERRULE	BRASS	NICKEL	1
5	WASHER	IRON	NICKEL	1
4	O-RING	RUBBER	RED	1
3	PIN	BRASS	GOLD	1
2	INSUKATON	PTFE	NONE	1
1	BODY	BRASS	Electrophoresis	1

-TOLERANCES-
UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 - 8mm ± 0.20mm
8 - 30mm ± 0.25mm
30 -120mm ± 0.30mm

BIG CAT CABLES

PART DESCRIPION:
WATERPROOF N CRIMP JACK FOR LMR400 CABLE

P/N: BC-202-400

Appd: JIM.KING	Date	Scale	Unit	Type	Page
Check:					
Draw: Gavin	2021.03.09	Free	MM	Z	1/1